

POSICONTROL Displays & Position controllers

lika.....



Series	PS611	TE601	PV1	LD200
Features	position controller	RDxx CANbus terminal	4 axis DRO	universal display
Display	LCD	LCD	LCD	LED 8 digit
Display mode	position, parameters	RDxx status, parameters	linear, mm/inch	linear, angular, mm/inch
Dimensions (mm)	120 x 154 x 34	120 x 154 x 34	280 x 110 x 35	96 x 48 x 49
Input	2 x AB	CAN	4 x AB0	AB0, 1Vpp, SSI, magnetic sensor
Counting frequency	20 kHz max.	-	2 MHz max.	500 kHz max.
Power supply	24 Vdc	24 Vdc	24 Vdc	24 Vdc
Interface	RS232, RS485, CAN	RS232, CAN	RS232	RS232, CAN
Output	8 x 24 V @ 500 mA	-	4 x ± 10 V 12 x 24 V @ 500 mA	3 x 24 V @ 50 mA

POSICONTROL Displays & Position controllers

lika.....



Series	MC150	MC111	MC221
Features	position display	position display	2 axis display
Display	LED 6 digit	LED 6 digit	2 x LED 6 digit
Display mode	linear, angular	linear, angular	linear, angular
Dimensions (mm)	96 x 72 x 71	96 x 72 x 60	96 x 96 x 72
Input	AB0	AB, Analogue	2 x AB
Counting frequency	500 kHz max.	25 kHz max.	90 kHz max.
Power supply	24 Vdc/Vac 115 Vac, 230 Vac	24 Vdc	24 Vdc/Vac 115 Vac, 230 Vac
Interface	RS232	-	RS232
Output	2 x 24 V @ 600 mA	2 x 24 V @ 600 mA	2 x 24 V @ 600 mA