



PRODUCT RANGE LIST

ORBIT BEARINGS INDIA PVT.LTD.

BEARING NUMBER	BOUNDARY DIMENSIONS								Load Rating		Limiting Speed		Weight kgs.	Abutment Dimensions								
	d mm	D mm	T mm	B mm	C mm	r ₁ mm	r mm	a mm	Dynamic Newtons	Static Newtons	Grease r.p.m.	Oil r.p.m.		d _a max	d _b min	D _a min	D _a max	D _b min	C _a min	C _b min	r _a max	r _b max
Metric Series																						
30204	20.000	47.000	15.250	14.000	12.000	1.0	1.0	11	27500	28000	8000	11000	0.120	27	26	40	41	43	2	3	1	1
30205	25.000	52.000	16.250	15.000	13.000	1.0	1.0	12	30800	33500	7500	10000	0.150	31	31	44	46	48	2	3	1	1
30206	30.000	62.000	17.250	16.000	14.000	1.0	1.0	14	40200	44000	6300	8500	0.230	38	36	53	56	57	2	3	1	1
30207	35.000	72.000	18.250	17.000	15.000	1.5	1.5	15	51200	56000	5300	7000	0.320	44	42	62	65	67	3	3	1	1
30208	40.000	80.000	19.750	18.000	16.000	1.5	1.5	16	61600	68000	4800	6300	0.420	49	47	69	73	74	3	3.5	1	1
30209	45.000	85.000	20.750	19.000	16.000	1.5	1.5	18	66000	76500	4500	6000	0.480	54	52	74	78	80	3	4.5	1	1
30210	50.000	90.000	21.750	20.000	17.000	1.5	1.5	19	76500	91500	4300	5600	0.540	58	57	79	83	85	3	4.5	1	1
30211	55.000	100.000	22.750	21.000	18.000	2.0	1.5	21	94600	113000	3900	5200	0.732	64	64	88	91	94	4	4.5	1.5	1.5
30212	60.000	110.000	23.750	22.000	19.000	2.0	1.5	22	99000	114000	3400	4500	0.880	70	69	96	101	103	4	4.5	1.5	1.5
30213	65.000	120.000	24.750	23.000	20.000	2.0	1.5	24	123000	148000	3100	4200	1.100	78	74	106	111	113	4	4.5	1.5	1.5
30214	70.000	125.000	26.250	24.000	21.000	2.0	1.5	25	125000	156000	3000	4000	1.250	82	79	110	116	118	4	5	1.5	1.5
30215	75.000	130.000	27.250	25.000	22.000	2.0	1.5	27	140000	176000	2800	3800	1.400	86	84	115	121	124	4	5	1.5	1.5
30216	80.000	140.000	28.250	26.000	22.000	2.5	2.0	28	151000	183000	2400	3400	1.600	92	90	124	130	132	4	6	2	2
30217	85.000	150.000	30.500	28.000	24.000	2.5	2.0	30	176000	220000	2200	3200	2.050	97	95	132	140	141	5	6.5	2	2
30220	100.000	180.000	37.000	34.000	29.000	3.0	2.5	35	246000	320000	1900	2800	3.650	116	112	157	168	168	5	8	2	2
30302	15.000	42.000	14.250	13.000	11.000	1.0	1.0	9	22400	20000	9000	13000	0.095	22	21	36	36	38	2	3	1	1
30305	25.000	62.000	18.250	17.000	15.000	1.5	1.5	13	48500	47500	6700	8900	0.272	34	32	54	55	57	2	3	1	1
30306	30.000	72.000	20.750	19.000	16.000	1.5	1.5	15	56100	56000	5600	7500	0.390	41	37	62	65	66	3	4.5	1	1
30307	35.000	80.000	22.750	21.000	18.000	2.0	1.5	16	72100	73500	5000	6700	0.520	46	44	70	71	74	3	4.5	1.5	1.5
30308	40.000	90.000	25.250	23.000	20.000	2.0	1.5	19	85800	95000	4500	6000	0.720	53	49	77	81	82	3	5	1.5	1.5
30309	45.000	100.000	27.250	25.000	22.000	2.0	1.5	21	108000	120000	4000	5300	0.970	59	54	86	91	92	3	5	1.5	1.5
30310	50.000	110.000	29.250	27.000	23.000	2.5	2.0	23	137000	152000	3700	4900	1.320	65	60	95	100	102	4	6	2	2
30311	55.000	120.000	31.500	29.000	25.000	2.5	2.0	24	142000	163000	3200	4300	1.550	71	65	104	110	111	4	6.5	2	2
30312	60.000	130.000	33.500	31.000	26.000	3.0	2.5	26	168000	196000	3000	4000	1.950	77	72	112	118	120	5	7.5	2	2
30313	65.000	140.000	36.000	33.000	28.000	3.0	2.5	29	204000	239000	2800	3800	2.560	84	77	122	128	130	5	8	2	2
31309	45.000	100.000	27.250	25.000	18.000	2.0	1.5	31	91300	102000	3400	4500	0.950	57	54	79	91	95	4	9	1.5	1.5
31312L	60.000	135.000	33.500	31.000	22.000	3.0	2.5	39	145000	166000	2600	3600	2.032	74	72	103	118	127	5	11.5	2	2
32010	50.000	80.000	20.000	20.000	15.500	1.0	1.0	18	61000	87000	4300	6000	0.379	57	56	72	74	77	4	4.5	1	1
32011	55.000	90.000	23.000	23.000	17.500	1.5	1.5	20	80900	116000	4000	5300	0.550	63	62	81	83	86	4	5.5	1	1

ORBIT BEARINGS INDIA PVT.LTD.

BEARING NUMBER	BOUNDARY DIMENSIONS								Load Rating		Limiting Speed		Weight	Abutment Dimensions								
	d mm	D mm	T mm	B mm	C mm	r ₁ mm	r mm	a mm	Dynamic Newtons	Static Newtons	Grease r.p.m.	Oil r.p.m.	kgs.	d _a max	d _b min	D _a min	D _a max	D _b min	C _a min	C _b min	r _a max	r _b max
32012	60.000	95.000	23.000	23.000	17.500	1.5	1.5	21	82500	122000	3800	5000	0.590	67	67	85	88	91	4	5	1	1
32013	65.000	100.000	23.000	23.000	17.500	1.5	1.5	22	84200	127000	3400	4500	0.630	72	72	90	93	97	4	5.5	1	1
32014	70.000	110.000	25.000	25.000	19.000	1.5	1.5	24	103000	157000	3200	4300	0.840	78	77	98	103	105	5	6	1	1
32015	75.000	115.000	25.000	25.000	19.000	1.5	1.5	25	110000	169000	3100	4200	0.930	83	82	103	108	110	5	6	1	1
32016	80.000	125.000	29.000	29.000	22.000	1.5	1.5	27	138000	216000	2600	3600	1.300	90	87	112	118	120	6	7	1	1
32017	85.000	130.000	29.000	29.000	22.000	1.5	1.5	28	140000	224000	2400	3400	1.350	94	92	117	123	125	6	7	1	1
32018	90.000	140.000	32.000	32.000	24.000	2.0	1.5	30	168000	270000	2200	3200	1.750	100	99	125	131	134	6	8	1.5	1.5
32019	95.000	145.000	32.000	32.000	24.000	2.0	1.5	31	182000	287000	2500	3300	1.880	105	104	130	136	139	6	8	1.5	1.5
32020	100.000	150.000	32.000	32.000	24.000	2.0	1.5	33	185000	298000	2400	3200	1.950	110	109	134	141	144	6	8	1.5	1.5
32021	105.000	160.000	35.000	35.000	26.000	2.5	2.0	34.5	201000	335000	2100	2800	2.420	116	115	143	150	154	6	9	2	2
32022	110.000	170.000	38.000	38.000	29.000	2.5	2.0	36	233000	390000	1800	2600	3.050	123	120	152	160	163	7	9	2	2
32206	30.000	62.000	21.250	20.000	17.000	1.0	1.0	15	50100	57000	6300	8500	0.280	37	36	52	56	58	3	4	1	1
32207	35.000	72.000	24.250	23.000	19.000	1.5	1.5	17	66000	78000	5300	7000	0.430	43	42	61	65	67	3	5	1	1
32208	40.000	80.000	24.750	23.000	19.000	1.5	1.5	19	74800	86500	4800	6300	0.530	49	47	68	73	75	3	5.5	1	1
32209	45.000	85.000	24.750	23.000	19.000	1.5	1.5	20	80900	98000	4500	6000	0.580	54	52	73	78	80	3	5.5	1	1
32210	50.000	90.000	24.750	23.000	19.000	1.5	1.5	21	82500	100000	4300	5600	0.610	58	57	78	83	85	3	5.5	1	1
32211	55.000	100.000	26.750	25.000	21.000	2.0	1.5	22	106000	129000	3800	5000	0.830	64	64	87	91	95	4	5.5	1.5	1.5
32212	60.000	110.000	29.750	28.000	24.000	2.0	1.5	24	125000	160000	3400	4500	1.150	69	69	95	101	104	4	5.5	1.5	1.5
32213	65.000	120.000	32.750	31.000	27.000	2.0	1.5	27	151000	193000	3000	4000	1.500	76	74	104	111	115	4	5.5	1.5	1.5
32214	70.000	125.000	33.250	31.000	27.000	2.0	1.5	28	157000	208000	2800	3800	1.600	80	79	108	116	119	4	6	1.5	1.5
32215	75.000	130.000	33.250	31.000	27.000	2.0	1.5	29	161000	212000	2600	3600	1.700	85	84	114	121	125	4	6	1.5	1.5
32216	80.000	140.000	35.250	33.000	28.000	2.5	2.0	30	187000	245000	2400	3400	2.050	91	90	122	130	134	5	7	2	2
32217	85.000	150.000	38.500	36.000	30.000	2.5	2.0	33	212000	285000	2200	3200	2.600	97	95	130	140	142	5	8.5	2	2
32218	90.000	160.000	42.500	40.000	34.000	2.5	2.0	36	251000	340000	2000	3000	3.350	102	100	138	150	152	5	8.5	2	2
32219	95.000	170.000	45.500	43.000	37.000	3.0	2.5	39	281000	390000	1900	2800	4.050	109	107	145	158	161	5	8.5	2	2
32220	100.000	180.000	49.000	46.000	39.000	3.0	2.5	41	319000	440000	1800	2600	4.900	115	112	154	168	171	5	10	2	2
32307	35.000	80.000	32.750	31.000	25.000	2.0	1.5	20	95200	106000	4800	6300	0.730	44	44	66	71	74	4	7.5	1.5	1.5
32308	40.000	90.000	35.250	33.000	27.000	2.0	1.5	23	117000	140000	4000	5300	1.000	51	49	73	81	82	3	8	1.5	1.5
32309	45.000	100.000	38.250	36.000	30.000	2.0	1.5	25	140000	170000	3600	4800	1.350	57	54	82	91	93	4	8	1.5	1.5
32310	50.000	110.000	42.250	40.000	33.000	2.5	2.0	27	172000	212000	3200	4300	1.800	63	60	90	100	102	5	9	2	2
32311	55.000	120.000	45.500	43.000	35.000	2.5	2.0	29	198000	250000	3000	4000	2.300	68	65	99	110	111	5	10.5	2	2

ORBIT BEARINGS INDIA PVT.LTD.

BEARING NUMBER	BOUNDARY DIMENSIONS								Load Rating		Limiting Speed		Weight	Abutment Dimensions								
	d mm	D mm	T mm	B mm	C mm	r ₁ mm	r mm	a mm	Dynamic Newtons	Static Newtons	Grease r.p.m.	Oil r.p.m.	kgs.	d _a max	d _b min	D _a min	D _a max	D _b min	C _a min	C _b min	r _a max	r _b max
32312	60.000	130.000	48.500	46.000	37.000	3.0	2.5	31	229000	290000	2600	3600	2.850	74	72	107	118	120	6	11.5	2	2
32313	65.000	140.000	51.000	48.000	39.000	3.0	2.5	35	266000	233000	2800	3800	3.450	80	77	117	128	130	6	12	2	2
32316	80.000	170.000	61.500	58.000	48.000	3.0	2.5	41	380000	500000	1900	2800	6.200	98	92	142	158	159	7	13.5	2	2
32317	85.000	180.000	63.500	60.000	49.000	4.0	3.0	42	402000	530000	1800	2600	6.850	103	99	150	166	167	7	14.5	2.5	2.5
33010	50.000	80.000	24.000	24.000	19.000	1.0	1.0	17	69300	102000	4500	6000	0.450	56	56	72	74	76	4	5	1	1
33012	60.000	95.000	27.000	27.000	21.000	1.5	1.5	20	91300	143000	3800	5000	0.710	67	67	85	88	90	5	6	1	1
33013	65.000	100.000	27.000	27.000	21.000	1.5	1.5	21	96800	156000	3400	4500	0.780	72	72	89	93	96	5	6	1	1
33016	80.000	125.000	36.000	36.000	29.500	1.5	1.5	26	168000	285000	2600	3600	1.650	90	87	112	118	119	6	6.5	1	1
33017	85.000	130.000	36.000	36.000	29.500	1.5	1.5	26	183000	310000	2600	3600	1.750	94	92	118	123	125	6	6.5	1	1
33018	90.000	140.000	39.000	39.000	32.500	2.0	1.5	27	216000	355000	2200	3200	2.200	100	99	127	131	135	7	6.5	1.5	1.5
33019	95.000	145.000	39.000	39.000	32.500	2.0	1.5	29	228000	378000	2200	3200	2.250	104	104	131	136	139	7	6.5	1.5	1.5
33020	100.000	150.000	39.000	39.000	32.500	2.0	1.5	29	224000	390000	2000	3000	2.400	109	109	135	141	143	7	6.5	1.5	1.5
33021	105.000	160.000	43.000	43.000	34.000	2.5	2.0	31	246000	430000	1900	2800	3.050	117	115	145	150	153	7	9	2	2
33022	110.000	170.000	47.000	47.000	37.000	2.5	2.0	34	281000	500000	1800	2600	3.850	123	120	152	160	161	7	10	2	2
33109	45.000	80.000	26.000	26.000	20.500	1.5	1.5	19	84200	114000	4500	6000	0.560	52	52	69	73	77	4	5.5	1	1
33111	55.000	95.000	30.000	30.000	23.000	1.5	1.5	22	110000	156000	3800	5000	0.860	63	62	83	88	91	5	7	1	1
33115	75.000	125.000	37.000	37.000	29.000	2.0	1.5	29	176000	265000	2800	3800	1.800	84	84	109	116	120	6	8	1.5	1.5
33116	80.000	130.000	37.000	37.000	29.000	2.0	1.5	30	179000	280000	2600	3600	1.900	89	89	114	121	126	6	8	1.5	1.5
33118	90.000	150.000	45.000	45.000	35.000	2.5	2.0	35	251000	390000	2000	3000	3.100	101	100	130	140	144	7	10	2	2
33208	40.000	80.000	32.000	32.000	25.000	1.5	1.5	21	105000	132000	4300	5600	0.770	47	47	67	73	76	5	7	1	1
33209	45.000	85.000	32.000	32.000	25.000	1.5	1.5	22	108000	143000	4000	5300	0.820	52	52	72	78	81	5	7	1	1
33210	50.000	90.000	32.000	32.000	24.500	1.5	1.5	23	109000	162000	3800	5000	1.950	57	57	77	83	87	5	7.5	1	1
33211	55.000	100.000	35.000	35.000	27.000	2.0	1.5	25	138000	190000	3400	4500	1.200	63	64	85	91	96	6	8	1.5	1.5
33213	65.000	120.000	41.000	41.000	32.000	2.0	1.5	30	191000	285000	3000	4000	4.540	75	74	102	111	115	6	9	1.5	1.5
33215	75.000	130.000	41.000	41.000	31.000	2.0	1.5	32	209000	300000	2400	3400	2.250	84	84	111	121	125	6	10	1.5	1.5
33216	80.000	140.000	46.000	46.000	35.000	2.5	2.0	36	250000	371000	2700	3600	2.990	89	90	119	130	135	7	11	2	2
33217	85.000	150.000	49.000	49.000	37.000	2.5	2.0	37	286000	430000	2000	3000	3.700	96	95	128	140	144	7	12	2	2
Inch Series																						
09067/9195	19.050	49.225	18.034	19.050	14.288	1.3	1.3	10	39100	40000	8000	11000	0.180	26	25.5	41	42.5	44	4	3.5	1	1
JLM104948/10	50.000	82.000	21.500	21.500	17.000	3.0	0.5	16	72100	100000	4500	6000	0.430	57	64	74	77	78	4	4.5	2.5	0.5
11162/11300	41.275	76.200	18.009	17.384	14.288	1.5	1.5	17	42500	51500	4900	6500	0.337	50	49	65	68	71	3	3.5	1	1

ORBIT BEARINGS INDIA PVT.LTD.

BEARING NUMBER	BOUNDARY DIMENSIONS								Load Rating		Limiting Speed		Weight	Abutment Dimensions								
	d mm	D mm	T mm	B mm	C mm	r ₁ mm	r mm	a mm	Dynamic Newtons	Static Newtons	Grease r.p.m.	Oil r.p.m.	kgs.	d _a max	d _b min	D _a min	D _a max	D _b min	C _a min	C _b min	r _a max	r _b max
11590/20	15.875	42.862	14.288	14.288	9.525	1.5	1.5	13	17600	17500	8700	12000	0.103	23	23	32	36	38	2	4.5	1	1
LM11949/10	19.050	45.237	15.494	16.637	12.065	1.3	1.3	10	27500	27500	8500	12000	0.120	25	25.5	38	38.5	41	3	3	1	1
M12649/10	21.430	50.005	17.526	18.288	13.970	1.3	1.3	11	36900	38000	8000	11000	0.170	28	28	43	43.5	46	3	3.5	1	1
14118/283	30.000	72.085	22.385	19.202	18.415	0.8	2.3	18	53900	67000	5600	7500	0.450	43	36.5	56	63	63	3	3.5	0.6	2
15120/245	30.213	62.000	19.050	20.638	14.288	0.8	1.3	13	46800	53900	6000	8000	0.260	38	40	54	55	58	4	4.5	0.6	1
15123/245	31.750	62.000	18.161	19.050	14.288	4.0	1.3	13	48400	57000	6000	8000	0.240	38	43.5	54	55	58	4	3.5	3	1
1988/22	28.575	57.150	19.845	19.355	15.875	3.5	1.5	14	47300	55000	6700	9000	0.220	35	40	49	49.5	54	3	3.5	3	1
HM218248/10	89.974	146.975	40.000	40.000	32.500	7.0	3.5	31	227000	340000	2400	3200	2.550	101	110.5	130	133.5	140	7	7.5	6	3
24780/20	41.275	76.200	22.225	23.020	17.462	3.5	0.8	17	68200	86500	5000	6700	0.430	48	48	65	64	71	4	4.5	3	0.6
25577/23	42.875	82.931	26.988	25.400	22.225	3.5	2.3	20	80900	106000	4500	6000	0.610	53	56.5	70	73	76	3	4.5	3	2
25590/20	45.618	82.931	23.812	25.400	19.050	3.6	0.8	17	83800	111000	4500	6000	0.540	53	57.5	71	76	76	5	4.5	3	0.6
2580/20	31.750	66.421	25.400	25.357	20.638	0.8	3.2	16	71400	85100	6000	8000	0.400	40	38	58	55	63	3	4.5	0.6	3
25877/21	34.925	73.025	23.812	24.608	19.050	1.5	0.8	15	72100	88000	5300	7000	0.470	44	42.5	62	66.5	67	5	4.5	1	0.6
27687/20	82.550	125.412	25.400	25.400	19.845	3.5	1.5	26	102000	163000	2700	3600	1.070	93	96	113	116	119	5	5.5	3	1
28580/21	50.800	92.075	24.608	25.400	19.845	3.6	0.8	20	84800	119000	4200	5600	0.720	61	63	79	85	86	5	4.5	3	0.6
28584/21	52.388	92.075	24.608	25.400	19.845	3.6	0.8	20	84800	119000	4200	5600	0.670	63	65	79	85	86	5	4.5	3	0.6
29685/20	73.025	112.712	25.400	25.400	19.050	3.5	3.3	26	95500	151000	3100	4100	0.873	82	86	100	100	108	4	6	3	3
LM29749/10	38.100	65.088	18.034	18.288	13.970	2.3	1.3	13	42900	57000	5600	7500	0.240	44	47.5	58	58	61	3	4	2	1
31594/20	34.925	76.200	29.370	28.575	23.812	1.5	3.3	20	85800	106000	5000	6700	0.630	44	43	62	64.5	71	4	5.5	1	3
33889/21	50.800	95.250	27.783	28.575	22.225	3.5	2.3	20	107000	139000	3900	5200	0.876	58	64	83	88	90	6	5.5	3	2
33895/22	53.975	95.250	27.783	28.575	22.225	1.5	0.8	20	107000	139000	3900	5200	0.824	61	62.5	83	88	90	6	5.5	1	0.6
3490/20	38.100	79.375	29.370	29.771	23.812	3.5	3.3	20	91300	110000	5000	6700	0.670	46	50	65	68	73	4	5.5	3	3
355X/352	44.450	90.119	23.000	21.692	21.808	3.5	2.3	16	70400	81500	4500	6000	0.660	55	56.5	76	77	80	3	3	3	2
359S/354X	46.038	85.000	20.638	21.692	17.462	2.3	1.5	16	70400	81500	4500	6000	0.490	55	56	76	77	80	3	3	2	1
368A/362A	50.800	88.900	20.638	22.225	16.513	3.6	1.2	16	74300	87300	4400	5800	0.500	58	63	80	81	83	4	4	3	1
3780/20	50.800	93.264	30.162	30.302	23.812	3.5	3.3	22	110000	146000	4000	5300	0.870	60	63	80	81.5	87	4	6	3	3
387/382	57.150	98.425	21.000	21.946	17.826	2.3	0.8	17	80900	102000	3800	5000	0.640	65	67.5	87	91.5	92	5	3	2	0.6
39581/20	57.150	112.712	30.162	30.162	23.812	8.0	3.3	23.5	138000	195000	3200	4200	1.400	76	79	100	100	107	5	6	7	3
395A/394A	66.675	110.000	22.000	21.996	18.824	0.8	1.3	21	89500	120000	3200	4300	0.796	77	74	98	101.5	105	4	3	0.6	1
3982/20	63.500	112.712	30.162	30.048	23.812	3.5	3.3	25	123000	183000	3200	4300	1.250	75	76.5	96	100	105	4	6	3	3
3984/20	66.675	112.712	30.162	30.048	23.812	3.5	3.3	25	123000	183000	3200	4300	1.150	75	79.5	96	100	105	4	6	3	3

ORBIT BEARINGS INDIA PVT.LTD.

BEARING NUMBER	BOUNDARY DIMENSIONS								Load Rating		Limiting Speed		Weight	Abutment Dimensions								
	d mm	D mm	T mm	B mm	C mm	r ₁ mm	r mm	a mm	Dynamic Newtons	Static Newtons	Grease r.p.m.	Oil r.p.m.	kgs.	d _a max	d _b min	D _a min	D _a max	D _b min	C _a min	C _b min	r _a max	r _b max
418/414	38.100	88.500	26.988	29.083	22.225	3.5	1.5	17	101000	114000	4800	6300	0.830	49	50	73	80.5	78	5	4.5	3	1
42687/20	76.200	127.000	30.162	31.000	22.225	3.5	3.3	27	138000	204000	2800	3800	1.450	88	89.5	112	114	120	5	7.5	3	3
462/453X	57.150	104.775	30.162	29.317	24.605	2.3	3.3	24	121000	160000	3600	4800	1.050	68	67.5	91	92.5	98	4	5.5	2	3
47487/20	69.850	120.000	32.545	32.545	26.195	3.6	3.3	26	166000	249000	3000	4000	1.460	81	83	105	107.5	113	6	6	3	3
482/472	69.850	120.000	29.794	29.007	24.237	3.5	2.0	26	132000	186000	3000	4000	1.350	80	83	103	110	112	4	5.5	3	1.5
LM48548/10	34.925	65.088	18.034	18.288	13.970	3.6	1.3	14	47300	57000	5600	7500	0.250	42	47	57	58	61	3	4	3.5	1
LM501349/10	41.275	73.431	19.558	19.812	14.732	3.5	0.8	16	55000	69500	4800	6300	0.330	48	53.5	64	67	69	4	4.5	3	0.6
HM518445/10	88.900	152.400	39.688	39.688	30.162	6.4	3.3	33	275000	404000	2000	3000	2.810	102	108.5	135	139	146	7	9.5	6	3
535/532A	44.450	111.125	38.100	36.957	30.162	3.6	3.3	26	159000	206000	3600	4800	1.830	64	57	90	95.5	97	5	7.5	3	3
537/532X	50.800	107.950	36.512	36.957	28.575	3.6	3.3	24	159000	206000	3600	4800	1.520	64	63.5	90	95.5	97	5	7.5	3	3
539/532X	53.975	107.950	36.512	36.957	28.575	3.6	3.3	24	159000	206000	3600	4800	1.450	64	66.5	90	95.5	97	5	7.5	3	3
566/563	69.850	127.000	36.512	36.170	28.575	3.6	3.3	28	182000	262000	2800	3800	1.900	83	83	109	114	119	5	7.5	3	3
567/563	73.025	127.000	36.512	36.170	28.575	3.6	3.3	28	182000	262000	2800	3800	1.790	83	86	109	114	119	5	7.5	3	3
575/572	76.200	139.992	36.512	36.098	28.575	3.5	3.3	31	187000	280000	2400	3400	2.450	94	89.5	120	127	131	5	7.5	3	3
580/572	82.550	139.992	36.512	36.098	28.575	3.6	3.3	31	191000	291000	2400	3400	2.140	94	96	120	127	131	5	7.5	3	3
582/572	82.550	139.992	36.512	36.098	28.575	6.9	3.3	31	191000	291000	2400	3400	2.110	94	102	120	127	131	5	7.5	6	3
593/592A	88.900	152.400	39.688	36.322	30.162	3.5	3.3	37	194000	305000	2000	3000	2.800	104	102.5	128	139	141	4	9.5	3	3
594A/592A	95.250	152.400	39.688	36.322	30.162	5.1	3.3	37	200000	319000	2000	3000	2.470	104	112	128	139	141	4	9.5	4	3
596/592A	85.725	152.400	39.688	36.322	30.162	3.5	3.3	37	194000	305000	2000	3000	2.900	96	102	128	139	141	4	9.5	3	3
598/592A	92.075	152.400	39.688	36.322	30.162	3.5	3.3	37	194000	305000	2000	3000	2.700	104	106	128	139	141	4	9.5	3	3
LM603049/11	45.242	77.788	19.842	19.842	15.080	3.5	0.8	17	53900	69500	4800	6300	0.370	52	57.5	68	71	74	4	4.5	3	0.6
621/612	53.975	120.650	41.275	41.275	31.750	3.5	3.3	27	172000	213000	3300	4400	2.210	69	63.5	98	108	108	6	9.5	3	3
6379/20	65.088	135.755	53.975	56.007	44.450	3.5	3.3	34	286000	400000	2800	3800	3.700	78	78.5	110	123	125	7	9.5	3	3
6386/20	66.675	135.755	53.975	56.007	44.450	4.3	3.3	34	286000	400000	2800	3800	3.650	78	81.5	110	123	125	7	9.5	4	3
LM67048/10	31.750	59.131	15.875	16.764	11.811	3.6	3.3	13	34700	41500	6300	8500	0.180	38	44.5	51	52	55	3	4	3.5	1
683/672	95.250	168.275	41.275	41.275	30.162	3.6	3.3	38	245000	386000	1900	2800	3.680	114	109	143	154.5	157	6	11	3	3
JM716649/10	85.000	130.000	30.000	29.000	24.000	3.0	2.5	30	149000	245000	2600	3600	1.360	94	99	115	118	125	5	6	2.5	2
72212/487	53.975	123.825	36.512	32.791	25.400	3.5	3.3	36	147000	180000	3800	5600	2.050	68	65.5	93	113	114	5	11	3	3
749A/742	82.550	150.089	44.450	46.672	36.512	3.5	3.3	32	261000	360000	2400	3200	3.370	95	96	130	137	142	8	7.5	3	3
HM903249/10	44.450	95.250	30.958	28.575	22.225	3.5	0.8	30	101000	122000	3600	4800	1.000	53	57	71	88	90	4	8.5	3	0.6