



Druck Pressure PB	DN	Ca. Maße Approx. Dimensions							Bestellzeichen Order-Code
		C	D	H	L	L2	L3		
315	13	30,2	24	51,0	151,0	6,7	35	FKH-3000-1/2"-4423	
315	20	38,1	32	73,0	162,0	6,7	35	FKH-3000-3/4"-4423	
315	24	44,4	38	76,0	178,0	8,0	35	FKH-3000-1"-4423	
250	32	50,8	43	105,0	190,5	8,0	35	FKH-3000-1 1/4"-4423	
200	38	60,3	50	111,4	231,0	8,0	40	FKH-3000-1 1/2"-4423	
200	48	71,4	62	130,0	232,0	9,5	45	FKH-3000-2"-4423	
400	13	31,7	24	51,0	151,0	7,7	35	FKH-6000-1/2"-4423	
400	20	41,3	32	73,0	174,0	8,8	40	FKH-6000-3/4"-4423	
400	24	47,6	38	76,0	198,0	9,5	40	FKH-6000-1"-4423	
400	32	54,0	44	105,0	223,0	10,3	45	FKH-6000-1 1/4"-4423	
400	38	63,5	51	111,4	281,0	12,6	70	FKH-6000-1 1/2"-4423	
400	48	79,4	67	130,0	316,0	12,6	80	FKH-6000-2"-4423	

Mit Flansch nach SAE J 518 / DIN 6162

3.000 PSI + 6.000 PSI

Für SAE-Flanschhälften, Rubrik 2.

1 = Kugeldichtung - POM

2 = Schwellendichtung - NBR

With Flange to SAE J 518 / DIN 6162

3.000 PSI + 6.000 PSI

For SAE-Split Flange Halves, Category 2.

1 = Ball Sealing - POM

2 = Stem Sealing - NBR