

VIBXPERT[®] II FFT Data Collector & Signal Analyzer



• Easy to use

The time is now Turn to PRÜFTECHNIK for innovative and proven technology

Driven by its motto – 'proven maintenance technology' – PRÜFTECHNIK has launched the VIBXPERT®II, the latest vibration data collector and signal analyzer based on sophisticated and refined technology.

A brilliant display yet long periods of use – VIBXPERT® II makes it possible!

VIBXPERT®II combines the proven features of its predecessor with the advantages of rapid processors and a brilliant energy-efficient color display. It demonstrates that the use of powerful components does not rule out low power consumption.

VIBXPERT® II is ...

- Intuitive to operate on its graphical user interface and effective use of color.
- Fast thanks to optimized measuring workflows and advanced processor technology.
- Ergonomic with a handy design and brilliant color display.
- Powerful due to many practical analysis functions and measuring templates.
- Long-lived with a long battery life and a large data memory.

Interfaces for industrial environments


Five industrial-proofed interfaces that are colored for easy identification connect to a wide variety of different sensor types and data links.




Simple to use with a wide range of applications



Meaningful icons offer guidance in selecting the measurement task.



Shaft vibration analysis with orbit, static shaft position and runout.



Narrow band and broadband monitoring of characteristic frequencies in the spectrum.

Title: Waterfall diagram for visualizing resonances.

Ergonomic and user-friendly

02 0.15	VIBX pert® //							
0.0 0.15	Roll.bear.enve		0 rpm	÷ (55%)	•	+		
Image <t< th=""><th>Channel A</th><th>R Main Delta</th><th></th><th></th><th>ESC</th><th>F</th></t<>	Channel A	R Main Delta			ESC	F		
0.1 0.05 0.05 0.05 15 15 15 15 15 15 15 15 15 1	[m/s ⁻]	B PA	RN	1S: 0.374 m/s²		1		
Frequency markers ↓ 2.Misalignment B Z Roller bearing ↓ 21201 ETN9 ↓ □ FTF □ BPFO ↓ □ BSF	0.1- 0.05-		a all all and		HELP	MEN		
	Frequer	ncy markers	ANTER 1 0	100 (H2)				
	→ 2 Roller → 2 120 - 0 - 0	bearing 01 ETN9 FTF BPFO BSF		A F	(
RPM 1140 1/min.		RPM	1140 1/min.					

Envelope spectrum of roller bearing inner race damage (BPFI) with identified side bands.

Status LEDs

- Traffic light display for the evaluation of results according to the ISO standard or user-defined alarm thresholds
- Device and battery status

Ergonomic keyboard

- One-thumb operation
- Illumination automatically adjusts to ambient light
- Non-slip grip

Brilliant color display

- 18-bit TFT LCD
- VGA (480 x 640 pixels)
- Non-reflective
- Automatic switch-off

Sturdy housing

- Light and compact
- Protection class IP 65


Large data memory

> 2 GB CompactFlash card

Powerful Li-ion battery

- 8-hour operating life
- Exchangeable

Simple to use with a wide range of applications



One- or two-channel coast-down test with RMS, amplitude or waterfall.



Field balancing in two planes. A 'smiley' appears when the required balancing grade is reached.



display of measuring locations.

VIBXPERT[®] in brief

Versatile

Route-based data collection Vibration diagnosis One- or two-plane field balancing Acceptance measurement with machine templates Troubleshooting Multimeter Data logging Visual inspection

Analysis in detail

Characteristic overall values & process parameters Time waveform Amplitude/envelope spectrum Cepstrum Phase, cross-channel phase Orbit Static shaft position Runout analysis (shaft vibration)

Bump test Coast-down/run-up test Order analysis Modal analysis **Operating Deflection Shape Analysis** (ODS) Transient capture Long-term recording Characteristic frequency markers Signal post-processing ISO standards for evaluation Valuable additional features

Printing of measurement reports Rugged hard case Extensive accessories Optional measuring functions that can be enabled by entering a password










OMNITREND® multiuser PC Software

OMNITREND[®] can be used to manage machine data, archive results in a database and enables the programming of measurement tasks and routes.

A wide range of evaluation and documentation functions are available. These are described more closely in the OMNITREND® brochure.



OMNITREND® supports the evaluation of collected machine data on a PC.

© Copyright 2010 by PRÜFTECHNIK AG. ISO 9001:2008 certified. VIBXPERT® and OMNITREND® are registered trademarks of PRÜFTECHNIK Dieter Busch AG. No copying or reproduction of this information, in any form whatsoever, may be undertaken without express written permission of PRÜFTECHNIK AG. The information contained in this leaflet is subject to change without further notice due to the PRÜFTECHNIK policy of continuous product development. PRÜFTECHNIK products are the subject of patents granted or pending throughout the world. Printed in Germany LIT 53.400.EN

PRÜFTECHNIK

Condition Monitoring GmbH Oskar-Messter-Str. 19-21 85737 Ismaning, Germany +498999616-0 Tel: Fax: +498999616-300 eMail: info@pruftechnik.com www.pruftechnik.com

A member of the PRÜFTECHNIK group