



NanoTechnology for excellent surfaces

In many areas there is a demand for water-repellent surfaces that are easy to clean. GBneuhaus provides a range of innovative nano-coatings, including the hydrophobic application **GBhydrophobic**, particularly for substrates like metal, plastics or glass.

gbneuhaus.de

sales@gbneuhaus.de





SUBSTRATES


- » plastics (polycarbonate, ethylene tetrafluoroethylene or polycarbonate films)
- » glass (borosilicate glass, soda-lime glass, quartz glass a.s.o.)
- » metals and alloys (e.g. steel, aluminium, copper, brass)

PROPERTIES

- » contact angle for water θ ≥ 105 ° (according to DIN 55660-3:2011-12)
- » maximum temperature load: 200 °C
- » transparent, individually coloured on request
- » combinable with antimicrobial function (SANPURE®)
- » film thickness from 150 up to 1.500 nm
- » no change in haptic quality of substrate
- » scratch-resistant (scratch hardness according to DIN EN ISO 1518 up to 20 N; pencil hardness according to DIN EN ISO 15184 up to 10 H)
- » abrasive hardness (cross-cut test according to DIN EN ISO 2409)
- » chemical-proof to customary detergents and disinfection methods
- » mechanically flexible









TECHNOLOGY

- » dip coating or spraying
- » application process is defined individually according to geometry and requirements of the substrate

COATING

- » certified according to REACH and RoHS
- » certified according to ISO 9001:2015; processes comply with IATF 16949
- » environmental management conforms to ISO 14001



GBneuhaus GmbHAm Herrnberg 10
98724 Neuhaus | Germany
phone: +49 3679 726030
fax: +49 3679 726033

sales@gbneuhaus.de