

## 13mm PVC Toothed Conveyor Belt for ceramic/marble polishing

### Details:

Top cover	Flex am
fabric	EM
Tension	60
Bottom thickness / profile	00
Top cover thickness / profile	H13
Color	petrol blue
Standard width mm	1000
Max. available width mm	2100
Belt thickness mm	13.0
Weight kg/m <sup>2</sup>	10.5
F/E at 1%	64
Number of plies	4
Material	PVC
Top hardness shore	75A
Top cover thickness mm	2.2
Laterally	stable
Flexing mm (20°C)	250
Back flexing mm (20°C)	350
Prolonged minimum °C	-15
Prolonged maximum °C	80
Short minimum °C	-15
Short maximum °C	100
Application	Processing machines for Ceramics, marble, tiles, stones

### Detailed descriptions:

- 1.Four layers of fabric, four layers of PVC
  - 2.Total thickness of 13mm
  - 3.The combination of fabric and pvc glue ensure the stability of the belts
  - 4.The top cogs possess belts with high drawing ability
  - 5.High strength PVC coats can endure high work pressure and resist abrasion.
  - 6.The bottom fabric can make sure the good collaborations between belts and equipment.
  - 7.High work efficiency and production capacity guarantee the sufficient products support and quick delivery.
- JRL has updated our equipment and innovates our producing technology to make sure the stability in performance.