

基本外形尺寸(mm) Boundary Dimensions				基本额定载荷(kN) Basic Load Ratings		极限转速(rpm) Limiting Speed		轴承型号 Designations	重量(kg) Mass
d	D	B	r1.2	Cr	Cor	Grease	Oil		≈
100	150	37	1.5	212	335	2200	2800	23020	2.31
	150	50	1.5	276	470	1800	2400	24020	3.08
	165	52	2	345	530	1700	2200	23120	4.38
	165	65	2	345	535	1600	2200	24120	5.42
	180	46	2.1	365	490	2400	3200	22220	4.84
	180	60.3	2.1	420	605	1600	2200	23220	6.6
	215	73	3	690	930	1900	2400	22320	12.7
110	170	45	2	293	465	2000	2400	23022	3.76
	170	60	2	380	645	1600	2200	24022	4.96
	170	60	2	380	645	1600	2200	24022	4.96
	180	56	2	385	630	1600	2000	23122	5.7
	180	69	2	460	750	1600	2000	24122	6.84
	200	53	2.1	485	645	2200	2800	22222	6.99
	200	69.8	2.1	515	760	1500	1900	23222	9.54
	240	50	3	450	545	1300	1700	21322	11.2
	240	80	3	825	1120	1700	2200	22322	17.6
120	180	46	2	315	525	1800	2200	23024	4.11
	180	60	2	395	705	1500	2000	24024	5.33
	180	60	2	395	705	1500	2000	24024	5.33
	200	62	2	465	720	1400	1800	23124	7.85
	200	80	2	575	950	1400	1800	24124	10
	215	58	2.1	550	765	2000	2600	22224	8.8
	215	76	2.1	630	970	1300	1700	23224	12.1
	130	200	52	2	400	655	1700	2000	23026
200		69	2	495	865	1400	1800	24026	7.84
200		69	2	495	865	1400	1800	24026	7.84
210		64	2	505	825	1300	1700	23126	8.69
210		80	2	590	1010	1300	1700	24126	10.7
230		64	3	655	940	1900	2400	22226	11
230		80	3	700	1080	1200	1600	23226	14.3
280		93	4	995	1350	1300	1600	22326	28.1
140		210	53	2	420	715	1600	1900	23028
	210	69	2	525	945	1300	1700	24028	8.37
	210	69	2	525	945	1300	1700	24028	8.37
	225	68	2.1	580	945	1200	1600	23128	10.5
	225	85	2.1	670	1160	1200	1600	24128	13
	250	68	3	645	930	1400	1700	22228	14.5
	250	88	3	835	1300	1100	1500	23228	18.8
	300	102	4	1160	1590	1200	1500	22328	35.4
150	210	45	2	334	622	1500	1700	23930	4.97
	225	56	2.1	470	815	1400	1800	23030	7.9

基本外形尺寸(mm) Boundary Dimensions				基本额定载荷(kN) Basic Load Ratings		极限转速(rpm) Limiting Speed		轴承型号 Designations	重量(kg) Mass
d	D	B	r1.2	Cr	Cor	Grease	Oil		≈
	225	75	2.1	590	1090	1200	1500	24030	10.5
	225	75	2.1	590	1090	1200	1500	24030	10.5
	250	80	2.1	725	1180	1100	1400	23130	15.8
	250	100	2.1	890	1530	1100	1400	24130	19.8
	250	100	2.1	890	1530	1100	1400	24130	19.8
	270	73	3	765	1120	1300	1600	22230	18.4
	270	96	3	975	1560	1100	1400	23230	24.2
	320	108	4	1220	1690	1100	1400	22330	41.5
160	220	45	2	360	675	1400	1800	23932	4.97
	220	60	2	393	807	1400	1800	24932	6.85
	240	60	2.1	540	955	1300	1700	23032	9.66
	240	80	2.1	680	1260	1100	1400	24032	12.7
	240	80	2.1	680	1260	1100	1400	24032	12.7
	270	86	2.1	855	1400	1000	1300	23132	20.3
	270	109	2.1	1040	1760	1000	1300	24132	25.4
	290	80	3	910	1320	1200	1500	22232	23.1
	290	104	3	1100	1770	1000	1200	23232	30.5
	340	114	4	1360	1900	1100	1300	22332	49.3
170	230	45	2	350	660	1400	1800	23934	5.38
	260	67	2.1	640	1090	1200	1600	23034	13
	260	90	2.1	825	1520	1000	1300	24034	17.3
	280	88	2.1	940	1570	1000	1300	23134	21.8
	280	109	2.1	1080	1860	1000	1300	24134	26.6
	310	86	4	990	1500	1100	1400	22234	28.8
	310	110	4	1200	1910	900	1200	23234	36.4
	360	120	4	1580	2110	1000	1200	22334	57.9
180	250	52	2	470	890	1200	1600	23936	7.64
	280	74	2.1	750	1270	1200	1400	23036	17.1
	280	100	2.1	965	1750	950	1200	24036	22.7
	280	100	2.1	965	1750	950	1200	24036	22.7
	300	96	3	1050	1760	900	1200	23136	27.5
	300	118	3	1190	2040	900	1200	24136	33.1
	320	86	4	1020	1540	1100	1300	22236	30.2
	320	112	4	1300	2110	850	1100	23236	38.9
	380	126	4	1740	2340	950	1200	22336	67
190	260	52	2	460	875	1200	1500	23938	8.03
	290	75	2.1	775	1350	1100	1400	23038	17.6
	290	100	2.1	975	1840	900	1200	24038	24
	320	104	3	1190	2020	850	1100	23138	34.5
	320	128	3	1370	2330	850	1100	24138	41.5
	320	128	3	1370	2330	850	1100	24138	41.5
	340	92	4	1140	1730	1000	1200	22238	35.5

基本外形尺寸(mm) Boundary Dimensions				基本额定载荷(kN) Basic Load Ratings		极限转速(rpm) Limiting Speed		轴承型号 Designations	重量(kg) Mass
d	D	B	r1.2	Cr	Cor	Grease	Oil		≈
	340	120	4	1440	2350	800	1100	23238	47.6
	400	132	5	1890	2590	900	1100	22338	78.1
200	280	60	2.1	570	1060	1100	1400	23940	11
	310	82	2.1	940	1700	1000	1300	23040	22.6
	310	109	2.1	1140	2120	850	1100	24040	30.4
	340	112	3	1360	2330	800	1000	23140	42.7
	340	140	3	1570	2670	800	1000	24140	51.3
	360	98	4	1300	2010	950	1200	22240	42.6
	360	128	4	1660	2750	750	1000	23240	57.1
	420	138	5	2000	2990	850	1000	22340	92.6
220	300	60	2.1	625	1240	1000	1300	23944	12.2
	340	90	3	1090	1980	950	1200	23044	29.7
	340	118	3	1360	2600	750	1000	24044	40.5
	370	120	4	1570	2710	710	950	23144	53
	370	150	4	1800	3200	710	950	24144	66.7
	400	108	4	1570	2430	850	1000	22244	59
	400	144	4	2020	3400	670	900	23244	80.4
	400	150	4	2040	3400	670	900	23244X2	81.9
	460	145	5	2350	3400	750	950	22344	116
240	320	60	2.1	635	1300	950	1200	23948	13.3
	360	92	3	1160	2140	850	1100	23048	32.6
	360	118	3	1390	2730	710	950	24048	43.4
	400	128	4	1790	3100	670	850	23148	66.9
	400	160	4	2130	3800	670	850	24148	79.5
	440	120	4	1870	2890	750	950	22248	80.2
	440	160	4	2440	4050	630	800	23248	106
	500	155	5	2600	3800	670	850	22348	147
260	320	45	2	366	883	850	1100	23852	8.05
	360	70	2.1	805	1590	850	1000	23952X2	21.6
	360	75	2.1	930	1870	850	1000	23952	23
	360	100	2.1	1070	2375	850	1100	24952	32
	400	104	4	1430	2580	800	950	23052	46.6
	400	140	4	1810	3500	630	850	24052	62.6
	440	144	4	2160	3750	600	800	23152	88.2
	440	180	4	2560	4700	600	800	24152	109
	480	130	5	2180	3400	670	850	22252	104
	480	174	5	2740	4550	560	750	23252	137
	540	165	6	3100	4600	630	800	22352	180
280	350	52	2	480	1121	800	1000	23856	12
	380	75	2.1	925	1950	800	950	23956	24.5
	380	100	2.1	1016	2327	800	1000	24956	34.5

基本外形尺寸(mm) Boundary Dimensions				基本额定载荷(kN) Basic Load Ratings		极限转速(rpm) Limiting Speed		轴承型号 Designations	重量(kg) Mass
d	D	B	r1.2	Cr	Cor	Grease	Oil		≈
	420	106	4	1540	2950	710	900	23056	50.5
	420	140	4	1880	3800	600	800	24056	66.4
	440	160	4	2180	4250	580	780	2656	88.6
	460	146	5	2230	4000	560	750	23156	94.3
	460	180	5	2640	5000	560	750	24156	115
	500	130	5	2280	3650	630	800	22256	110
	500	176	5	2880	4900	530	670	23256	147
	580	175	6	3500	5150	560	710	22356	221
300	380	60	2.1	612	1482	700	900	23860	17
	420	90	3	1230	2490	710	900	23960	38.2
	460	118	4	1920	3700	670	850	23060	70.5
	460	160	4	2310	4600	530	710	24060	93.6
	500	160	5	2670	4800	500	670	23160	125
	500	200	5	3100	5800	500	670	24160	152
	540	140	5	2610	4250	600	750	22260	139
	540	192	5	3400	5900	480	630	23260	189
	620	185	7.5	3950	5900	400	520	22360	264
320	400	60	2.1	639	1577	950	1300	23864	17.5
	400	80	2.1	870	2210	900	1200	24864	22.8
	440	90	3	1300	2750	670	850	23964	40.6
	480	121	4	1960	3850	630	800	23064	75.6
	480	160	4	2440	5050	500	670	24064	99.7
	540	176	5	3050	5500	480	600	23164	162
	540	218	5	3550	6650	480	600	24164	196
	580	150	5	2990	4850	530	670	22264	174
	580	208	5	3900	6900	450	600	23264	239
	580	213	5	4000	7050	450	600	23264X2	241
	670	200	7.5	4250	6550	400	530	22364	356
340	420	60	2.1	655	1643	630	800	23868	18.5
	460	90	3	1330	2840	630	800	23968	42.4
	520	133	5	2280	4400	560	710	23068	101
	520	180	5	2920	6050	480	600	24068	135
	580	190	5	3600	6600	430	560	23168	206
	580	243	5	4250	7900	430	560	24168	257
	620	165	6	3450	5600	430	560	22268	226
	620	224	6	4400	7800	400	530	23268	295
	710	212	7.5	5000	7800	360	480	22368	422
360	440	60	2.1	677	1767	600	750	23872	20
	480	72	3	1090	2350	630	800	22972	37.1
	480	90	3	1390	3050	600	750	23972	44.7
	540	134	5	2390	4700	530	670	23072	106
	540	180	5	2930	6100	450	600	24072	139

基本外形尺寸(mm) Boundary Dimensions				基本额定载荷(kN) Basic Load Ratings		极限转速(rpm) Limiting Speed		轴承型号 Designations	重量(kg) Mass
d	D	B	r1.2	Cr	Cor	Grease	Oil		≈
	600	192	5	3800	7100	400	530	23172	217
	600	243	5	4200	8000	400	530	24172	264
	650	170	6	3553	5890	600	750	22272	255
	650	232	6	4800	8550	380	500	23272	342
	750	224	7.5	5500	8650	360	480	22372	503
380	520	106	4	1870	4100	530	670	23976	65.4
	560	135	5	2500	5100	530	630	23076	113
	560	180	5	3050	6600	430	560	24076	148
	620	194	5	4000	7600	400	500	23176	229
	620	243	5	4350	8450	400	500	24176	275
	680	175	6	4050	6950	380	480	22276	288
	680	240	6	5150	9200	360	480	23276	372
	680	245	6	5250	9650	360	480	23276X2	382
	780	230	7.5	5850	9300	340	450	22376	554
400	500	100	2.1	1330	3500	600	800	24880	45.3
	540	106	4	1890	4250	530	630	23980	69.1
	600	148	5	2970	5900	480	600	23080	146
	600	200	5	3600	7600	400	500	24080	193
	650	200	6	4150	7900	380	480	23180	257
	650	250	6	4950	10100	380	480	24180	316
	720	185	6	4550	7650	360	450	22280	343
	720	256	6	5800	10400	340	450	23280	449
	720	260	6	5850	10600	340	450	23280X2	457
	820	243	7.5	6232	9880	360	450	22380	650
420	520	75	2.1	1090	2710	530	630	23884	34.8
	560	106	4	1870	4250	500	600	23984	71.6
	620	150	5	2910	5850	450	560	23084	151
	620	200	5	3750	8100	380	480	24084	199
	700	224	6	5000	9400	340	450	23184	341
	700	280	6	6000	12000	340	450	24184	421
	760	195	7.5	5000	8300	320	430	22284	405
	760	272	7.5	6450	11700	320	430	23284	534
	850	250	9.5	6800	11000	300	400	22384	704
440	600	118	4	2190	4800	450	560	23988	96.3
	650	157	6	3150	6350	430	530	23088	173
	650	212	6	4150	9100	360	450	24088	237
	720	226	6	5300	10300	320	430	23188	360
	720	280	6	6000	12100	320	430	24188	433
	790	200	7.5	5300	8800	320	420	22288	446
	790	280	7.5	6900	12800	300	400	23288	594
	790	285	7.5	6900	12800	300	400	23288X2	595
	900	265	9.5	7650	12500	300	400	22388	844

基本外形尺寸(mm) Boundary Dimensions				基本额定载荷(kN) Basic Load Ratings		极限转速(rpm) Limiting Speed		轴承型号 Designations	重量(kg) Mass
d	D	B	r1.2	Cr	Cor	Grease	Oil		≈
460	580	118	3	1700	4655	450	560	24892	75.5
	620	118	4	2220	4950	430	530	23992	100
	620	140	4	2440	6000	420	520	24992X2	122
	680	163	6	3450	7100	400	500	23092	201
	680	218	6	4500	9950	340	430	24092	266
	760	240	7.5	5700	10900	300	400	23192	423
	760	300	7.5	6300	12400	300	400	24192	512
	830	212	7.5	5850	10200	300	400	22292	530
	830	296	7.5	7350	13700	280	380	23292	691
	950	280	9.5	8500	14000	260	360	22392	1000
480	600	90	3	1368	3562	430	530	23896	61
	650	128	5	2580	5850	400	500	23996	121
	700	165	6	3800	7950	400	480	23096	211
	700	218	6	4600	10200	320	430	24096	270
	790	248	7.5	6050	11700	300	380	23196	475
	790	308	7.5	7150	14600	300	380	24196	567
	870	224	7.5	6400	11200	280	380	22296	613
	870	310	7.5	7850	14400	260	360	23296	795
	980	290	9.5	9000	15000	260	360	22396	1100
	500	620	90	3	1406	3800	430	530	238/500
670		128	5	2460	5550	400	500	239/500	124
670		170	5	3250	8000	380	480	249/500	175
720		167	6	3750	8100	380	480	230/500	220
720		218	6	4450	9900	300	400	240/500	276
830		264	7.5	6850	13400	280	360	231/500	567
830		325	7.5	8000	16000	280	360	241/500	666
920		336	7.5	9000	16600	260	320	232/500	969
530		650	118	3	1748	5035	380	480	248/530
	710	136	5	2930	6800	360	450	239/530	149
	710	180	5	3650	9000	340	430	249/530	208
	780	185	6	4400	9200	340	430	230/530	298
	780	250	6	5400	11800	280	360	240/530	390
	870	272	7.5	7150	14100	260	340	231/530	628
	870	335	7.5	8500	17500	260	340	241/530	773
	980	355	9.5	10100	18800	240	300	232/530	1170
	560	680	90	3	1650	4450	360	460	238/560
750		140	5	3100	7250	340	430	239/560	172
750		190	5	4050	10200	320	400	249/560	246
820		195	6	5000	10700	320	400	230/560	344
820		258	6	5950	13300	260	340	240/560	440
920		280	7.5	7850	15500	240	320	231/560	727

基本外形尺寸(mm) Boundary Dimensions				基本额定载荷(kN) Basic Load Ratings		极限转速(rpm) Limiting Speed		轴承型号 Designations	重量(kg) Mass
d	D	B	r1.2	Cr	Cor	Grease	Oil		≈
	920	355	7.5	9400	19600	240	320	241/560	886
	1030	365	9.5	10900	20500	220	280	232/560	1320
600	800	150	5	3450	8100	320	400	239/600	205
	800	200	5	4500	11400	320	380	249/600	292
	870	200	6	5450	12200	300	360	230/600	389
	870	272	6	6600	15100	240	320	240/600	529
	980	300	7.5	8750	17500	220	280	231/600	898
	980	375	7.5	10400	21900	220	280	241/600	1050
	1090	388	9.5	12700	24900	200	260	232/600	1590
	1090	412	12	13400	25600	180	240	232/600	1850
630	780	112	4	2080	5795	320	400	238/630	120
	780	150	4	3050	8800	320	380	248/630	158
	850	145	6	3450	7950	300	380	239/630X2	227
650	850	165	6	4000	9350	300	360	239/630	259
	850	212	6	5200	12900	280	360	249/630	371
	920	212	7.5	5900	12700	280	340	230/630	468
	920	290	7.5	7550	17700	220	300	240/630	637
	1030	315	7.5	9600	19400	200	260	231/630	1040
	1030	400	7.5	11300	23900	200	260	241/630	1250
	1150	412	12	13400	25600	180	240	232/630	1850
670	820	112	4	2137	6080	280	360	238/670	130
	900	170	6	4350	10300	260	340	239/670	300
	900	230	6	5700	14600	260	340	249/670	433
	920	170	6	4350	10300	260	340	239/670X1	343
	980	230	7.5	6850	15000	240	320	230/670	571
	980	308	7.5	8450	19500	200	260	240/670	773
	1090	336	7.5	10600	21600	190	240	231/670	1230
	1090	412	7.5	12400	26500	190	240	241/670	1440
	1220	438	12	14900	28700	170	220	232/670	2210
710	950	180	6	4800	11700	240	300	239/710	352
	950	243	6	5576	14820	200	280	249/710	495
	1030	236	7.5	7100	15800	240	280	230/710	647
	1030	315	7.5	8850	20700	190	240	240/710	861
	1150	345	9.5	11800	24500	180	240	231/710	1420
	1150	438	9.5	13900	30500	170	220	241/710	1730
	1280	450	12	15700	30500	160	200	232/710	2470
	1280	475	12	16500	31500	160	200	232/710	2600
750	920	128	5	2783	8075	240	320	238/750	135
	1000	185	6	5250	12800	220	280	239/750	398
	1000	200	6	5250	12800	220	280	239/750X2	433
	1000	250	6	7750	17200	190	260	249/750	560
	1090	250	7.5	7750	17200	220	260	230/750	768

基本外形尺寸(mm) Boundary Dimensions				基本额定载荷(kN) Basic Load Ratings		极限转速(rpm) Limiting Speed		轴承型号 Designations	重量(kg) Mass
d	D	B	r1.2	Cr	Cor	Grease	Oil		≈
	1090	335	7.5	10100	24000	180	220	240/750	1030
	1220	365	9.5	13100	27300	160	200	231/750	1700
	1220	475	9.5	17600	40500	160	200	241/750	2290
	1360	475	15	17700	35500	140	190	232/750	2980
800	980	180	5	3933	12255	180	240	248/800	300
	1060	195	6	5600	13700	220	260	239/800	462
	1060	258	6	7500	20000	220	240	249/800	646
	1150	258	7.5	8350	19100	200	240	230/800	870
	1150	280	7.5	8350	19100	180	220	230/800X2	941
	1150	345	7.5	10900	26300	160	200	240/800	1130
	1280	375	9.5	13800	29200	150	190	231/800	1870
	1280	475	9.5	17480	38475	130	170	241/800	2300
	1420	488	15	20300	41000	130	170	232/800	3250
850	1030	136	5	3173	9500	190	260	238/850	240
	1120	200	6	6100	15200	190	240	239/850	523
	1120	272	6	7760	21660	170	220	249/850	740
	1220	272	7.5	9300	21400	180	220	230/850	1020
	1220	290	7.5	9150	22000	180	220	230/850X2	1103
	1220	305	7.5	9300	23500	170	220	230/850X2	1170
	1220	330	7.5	11000	26900	160	210	240/850X2	1203
	1220	365	7.5	11600	28300	150	190	240/850	1350
	1360	400	12	15800	34000	130	180	231/850	2260
	1360	500	12	21200	48000	130	170	241/850	2970
	1500	515	15	22300	45500	120	160	232/850	3890
900	1090	190	5	4427	14535	170	220	248/900	370
	1180	206	6	6600	16700	180	220	239/900	591
	1180	280	6	9150	24500	170	220	249/900	852
	1280	280	7.5	9850	22800	160	200	230/900	1160
	1280	305	7.5	10300	24800	160	200	230/900X2	1250
	1280	375	7.5	12800	31500	140	180	240/900	1520
	1420	412	12	17000	37000	120	160	231/900	2490
	1580	515	15	23400	47500	110	140	232/900	4300
950	1250	224	7.5	7600	19900	160	200	239/950	732
	1250	300	7.5	8740	24700	140	180	249/950	1000
	1360	300	7.5	11300	26500	150	190	230/950	1400
	1360	320	7.5	11500	28000	130	180	230/950X2	1447
	1360	412	7.5	14500	36500	120	160	240/950	1880
	1400	300	7.5	11400	25200	120	160	230/950X1	1570
	1660	530	15	24700	50500	100	130	232/950	4800
1000	1220	165	6	4427	13585	160	200	238/1000	410
	1220	218	6	6550	20800	160	200	248/1000	567

基本外形尺寸(mm) Boundary Dimensions				基本额定载荷(kN) Basic Load Ratings		极限转速(rpm) Limiting Speed		轴承型号 Designations	重量(kg) Mass
d	D	B	r1.2	Cr	Cor	Grease	Oil		≈
	1320	236	7.5	8200	21700	150	190	239/1000	881
	1320	258	7.5	8500	22600	150	190	239/1000X2	911
	1320	315	7.5	9880	27550	140	170	249/1000	1200
	1420	308	7.5	11900	28100	140	170	230/1000	1560
	1420	320	7.5	11500	28400	120	160	230/1000	1630
	1420	412	7.5	15300	38500	110	150	240/1000	2010
	1580	462	12	20330	45600	100	140	231/1000	3500
	1580	580	12	21375	47500	100	130	241/1000	4300
1060	1280	165	6	4530	14250	140	180	238/1060	435
	1280	218	6	5795	19000	140	180	248/1060	570
	1400	250	7.5	9300	24400	130	170	239/1060	1030
	1400	335	7.5	10925	30875	130	170	249/1060	1400
	1500	325	9.5	13000	31500	120	160	230/1060	1790
	1500	340	9.5	13000	31500	110	140	230/1060X2	1850
	1500	438	9.5	16800	43000	100	130	240/1060	2410
1120	1360	180	6	6200	18700	140	180	238/1120	536
	1360	243	6	6887	22800	130	170	248/1120	735
	1460	250	7.5	9500	26000	120	160	239/1120	1100
	1460	335	7.5	11115	32775	110	140	249/1120	1500
	1580	345	9.5	15400	38000	110	140	230/1120	2120
	1580	360	9.5	14700	36000	110	140	230/1120X2	2230
	1580	380	9.5	15500	38500	100	130	230/1120X2	2330
	1580	462	9.5	18700	49500	95	120	240/1120	2790
1180	1420	180	6	5576	17670	120	160	238/1180	575
	1420	243	6	7324	25650	120	160	248/1180	770
	1540	272	7.5	10545	29450	110	140	239/1180	1400
	1540	355	7.5	12635	37050	100	130	249/1180	1800
	1660	475	9.5	20200	52500	85	110	240/1180	3180
1250	1500	250	6	8800	30000	90	120	248/1250	918
	1630	280	7.5	11600	31500	85	110	239/1250	1540
	1630	375	7.5	15600	45000	85	110	249/1250	2150
	1750	375	9.5	17005	42750	80	100	230/1250	2840
	1750	390	9.5	17400	44500	80	100	230/1250X2	2860
	1750	400	9.5	18000	46000	75	100	230/1250X2	2970
	1750	500	9.5	21000	59500	75	100	240/1250	3700
1320	1600	280	6	9291	31825			248/1320	1160
	1720	300	7.5	13600	38000			239/1320	1900
	1720	350	7.5	13500	38500			239/1320X2	2100
	1720	400	7.5	15295	46550			249/1320	2500
	1850	480	12	21200	58500			240/1320X2	4060
	1850	530	12	22600	63500			240/1320	4400

基本外形尺寸(mm) Boundary Dimensions				基本额定载荷(kN) Basic Load Ratings		极限转速(rpm) Limiting Speed		轴承型号 Designations	重量(kg) Mass
d	D	B	r1.2	Cr	Cor	Grease	Oil		≈
1400	1700	300	7.5	12000	40500			248/1400	1500
	1820	315	9.5	14300	40500			239/1400	2140
	1820	425	9.5	20000	58500			249/1400	3020
	1950	545	12	24500	65000			240/1400	4900
1500	1820	315	7.5	11115	38475			248/1500	1700
	1950	335	9.5	16000	47500			239/1500	2800
	1950	450	9.5	19665	59850			249/1500	3550

SYB BEARINGS