



型号 Size	类型 Type	锥孔号 Bushing NO.	最大孔径 Max Bore	A	B	C	F	L	扳手空间 Wrench Space	净重/Kg Weight/Kg
F040	B	H7	32	104	—	82	9	33.0	—	1.00
	F	1008	25		—			33.0	29	0.85
	H	1008	25		—			33.0	29	0.85
F050	B	H7	38	133	79	100	11	45.0	—	1.89
	F	1210	32		79			38.0	38	1.10
	H	1210	32		79			38.0	38	1.05
F060	B	H7	45	165	103	125	14.5	55.0	—	3.52
	F	1610	42		103			42.0	38	1.80
	H	1610	42		103			42.0	38	1.85
F070	B	H7	50	187	80	144	8.5	47.0	—	3.17
	F	2012	50		80			44.0	42	2.45
	H	1610	42		80			42.0	38	2.55
F080	B	H7	60	211	98	167	11	55.0	—	5.24
	F	2517	65		98			58.0	48	3.60
	H	2012	50		98			45.0	42	3.70
F090	B	H7	70	233	108	188	11.5	63.5	—	7.53
	F	2517	65		108			59.5	48	5.65
	H	2517	65		108			59.5	48	5.6
F100	B	H7	80	254	120	216	12	70.5	—	10.93
	F	3020	80		120			65.5	55	7.15
	H	2517	65		113			65.5	48	8.00
F110	B	H7	90	279	134	233	12.5	75.5	—	13.50
	F	3020	80		134			63.5	55	9.45
	H	3020	80		134			63.5	55	9.95
F120	B	H7	100	314	140	264	10.5	84.5	—	19.20
	F	3525	100		140			79.5	67	13.45
	H	3020	80		140			65.5	55	13.55
F140	B	H7	130	359	178	311	10	110.5	—	31.81
	F	3525	100		178			81.5	67	22.9
	H	3525	100		178			81.5	67	24.2
F160	B	H7	140	402	197	345	11	117.0	—	42.53
	F	4030	115		197			92.0	80	31.75
	H	4030	115		197			92.0	80	31.5
F180	B	H7	150	470	205	398	11	137.0	—	57.60
	F	4535	125		205			112.0	89	48.00
	H	4535	125		205			112.0	89	48.00
F200	B	H7	150	508	205	429	12.5	138.0	—	71.50
	F	4535	125		205			113.0	89	66.1
	H	4535	125		205			113.0	89	66.00
F220	B	H7	160	562	223	474	27.5	154.5	—	90.00
	F	5040	125		223			129.5	92	77.00
	H	5040	125		223			129.5	92	77.00
F250	B	H7	190	628	254	532	29.5	161.5	—	112.00

轮胎联轴器  
Tyre Coupling



型号 Size	最大转速 Max.Speed (RPM)	额定扭矩 Torque (NM)	最大扭矩 Max Torque (NM)	最大偏心量 Max.Parallel Misalignment(mm)	最大轴向窜动 Max.EndFloat (mm)	螺丝尺寸 Screw Size	螺钉数量 Screw NO.	螺钉扭矩 Screw Torque (NM)
F040	4500	25	65	1.1	1.3	M5	4	6
F050	4500	65	160	1.3	1.7	M6	4	11
F060	4000	125	320	1.6	2	M6	5	11
F070	3600	250	490	1.9	2.3	M8	5	28
F080	3100	380	760	2.1	2.6	M8	6	28
F090	3000	500	1100	2.4	3	M10	6	55
F100	2600	670	1520	2.6	3.3	M10	6	55
F110	2300	880	2140	2.9	3.7	M12	6	55
F120	2100	1330	3550	3.2	4	M12	6	99
F140	1800	2330	5640	3.7	4.6	M16	8	99
F160	1600	3770	9340	4.2	5.3	M20	8	245
F180	1500	6270	16450	4.8	6	M16	12	245
F200	1300	9330	23500	5.3	6.6	M20	12	245
F220	1100	11600	33120	5.8	7.3	M20	12	477
F250	1000	14680	42740	6.6	8.2	M20	16	477

$$\text{Torque/扭矩 (NM)} = 9550 \times \frac{\text{Design Power/设计功率 (KW)}}{\text{Motor Speed/电机转速 (rpm)}}$$