



深圳市盛格纳电子有限公司

Shenzhen Signal Electronics Co., Ltd

SIGNAL ELECTRONICS (HK) CO., LIMITED



Your Reliable Partner in Connectivity !

M12 X

- **M12 X-coding**
- **8 contacts**
- **Ethernet , Profinet** application
- **With Cat5/Cat5e/Cat6/Cat7** cables
- **4 twin data transmission up to 10 Gbit/s**
- **-40°C-85°C** temperature range
- **0.5A** rated current
- **800V** rated impulse voltage
- **IP67** degree of protection
- **Cable assembly/Panel mount type**
Field attachable type/Crimp type are available
- **In accordance with DIN IEC 61076-2-109**



M12 D

- **M12 D-coding**
- **4 contacts**
- **Max 20AWG/0.75mm²** wire gauge
- **Data transmission up to 100MHz**
- **-40°C-85°C** temperature range
- **4A** rated current
- **2500V** rated impulse voltage
- **IP67** degree of protection
- **Cable assembly/Panel mount type**
Field attachable type/Crimp type are available
- **In accordance with DIN IEC 61076-2-101**



M12 T



- **M12 T-coding**
- **4 contacts**
- **Max 16AWG/1.5mm² wire gauge**
- **-40°C-85°C temperature range**
- **12A rated current**
- **1500V rated impulse voltage**
- **IP67 degree of protection**
- **Cable assembly/Panel mount type**
Field attachable type/Crimp type are available
- **In accordance with DIN EN 61076-2-111**

M12 S

- **M12 S-coding**
- **3/4 contacts**
- **Max 16AWG/1.5mm² wire gauge**
- **-40°C-85°C temperature range**
- **16A/12A rated current**
- **6000V rated impulse voltage**
- **IP67 degree of protection**
- **Cable assembly/Panel mount type**
Field attachable type are available
- **In accordance with DIN EN 61076-2-111**



M12 L



- **M12 L-coding**
- **5 contacts**
- **Max 16AWG/1.5mm² wire gauge**
- **-40°C-85°C temperature range**
- **16A rated current**
- **1500V rated impulse voltage**
- **IP67 degree of protection**
- **Cable assembly/Panel mount type**
Field attachable type are available
- **In accordance with DIN EN 61076-2-111**



M8 P

- **M8 P-coding**
- **4 contacts**
- **22AWG/0.34mm² wire gauge**
- **-40°C-85°C temperature range**
- **4A rated current**
- **60V rated voltage**
- **IP67 degree of protection**
- **Cable assembly/Panel mount type**
Field attachable type



M5 series



M8 series



M9 series



M12 series



M16 series



M23 series



USB/D-Sub



RF



Distribution box





联系我们/contact us



Shenzhen Signal Electronics Co., Ltd
SIGNAL ELECTRONICS (HK) CO., LIMITED
深圳市盛格纳电子有限公司

International Sales/国际销售 : +86 0755 86250720 / +86 0755 27153782

Domestic Sales/国内销售 : +86 0755 29886112

Fax/传真 : +86 0755 29886179

Add/厂址 : Building 15, Xia Lang Industrial Park, He Shui Kou Community,
Matian Residential District, Guangming New District, Shenzhen, GD, China

广东省深圳市光明新区马田街道合水口社区下朗工业区15栋

Email/电邮 : sales@sz-signal.com / info@sz-signal.com

Website/网站 : www.sz-signal.com / www.signal-connector.com