



## ELECTROMECHANICAL LUBRICATOR

**THE EFFICIENT AND ECONOMIC SOLUTION  
FOR SINGLE LUBRICATION POINTS**



- 3 versions available
- electromechanical drive
- 10 bar (145 psi)
- up to 24 months per filling
- refillable up to 5 times  
without any follow-up costs  
\* within a maximum of 48 months
- oil or grease up to NLGI cl. 2
- self-filling possible
- - 20 °C to + 60°C  
\* with suitable lubricant



# Automatic Lubrication of bearings, chains, open tooth systems and linear motions

## TECHNICAL DATA

	Lub5-120	Lub5-120 PLUS	Lub5-250
Runtime per filling	1 / 3 / 6 / 12 / 24 months		
Volume	120ml	120ml	250ml
Discharges	max. 6 (=720ml)	max. 6 (=720ml)	max. 6 (=1500ml)
Diameter x height	127 x 70mm	182 x 70mm	243 x 70mm
Fixing thread	External thread R1/4		
Filling	empty / standard filling / special filling		
Battery capacity	Standard	triple suited for high counterpressure and low temperatures	Standard




UP TO  
**24**  
MONTHS

OPERATING  
PRESSURE  
**10**  
BAR

MAX  
**48**  
MONTHS  
LIFETIME

REFILL  
  
**5x**

LED  
  
DISPLAY

MOUNTING  
  
IN ANY  
POSITION

MICRO  
CONTROLLER  


BATTERY  
POWERED  




Easy filling  
by grease gun



refillable  
anytime

