

Kuhnke Vico Control Technology

Kuhnke Vico 1500

Touch Display

Kuhnke Vico is a control and display monitor with a high-quality and long-life TFT display backlit by LEDs for industrial applications. Image information is exchanged through the unit's digital DVI port. Touch screen input is transferred via USB.

A seamless sealing film protects its front against dust, dirt and spray water in conformity with IP 65. The units' extended temperature range gives operators a plus in safety.

Features

- DVI video port
- 15" touch screen
- LED backlighting
- Seamless front panel
- Integrated USB hub
- IP 65 front panel



Technical data	
Туре	Kuhnke Vico 1500
Screen size / resolution	15" / XGA, 1024 x 768
Touch screen	4-wire analogue resistive
Backlight	White LED, service life > 50000 h
Brightness / contrast ratio	400 cd/m² / 700:1
Video port	DVI D
Touch screen port	USB
USB hub	2 x USB (USB 2.0 / USB 1.1, female type A)
Housing	IP 20, galvanised steel sheet casing Installs in any rack, cabinet, desks or swivel frames
Front panel	IP 65, aluminium with seamless film cover (RAL 7035) for protection against dust, dirt and splash water
Status indication	Front-fitted Power LED
Outer dimensions (W x H x D)	394 mmx 326 mm x 53 mm
Power supply	24 V DC / (1032)
Power output	Approx. 10 W (@ 24 V DC)

¹Technical Details of panel PC variant Kuhnke Vico 1508

We reserve the rights of modification, omission, error with respect to the products. Illustrations similar. All rights reserved by the individual copyright holders. EtherCAT® is registered trademark and patented technology, licensed by Beckhoff Automation GmbH, Germany, Microsoft®, Windows® and the Windows® Logo are registered trademarks of Microsoft Corporation in the USA and other countries. At www.picopen.org you will find more information about PLCopen Organisation. CiA® and CANopen® are registered community trademarks of CAN in Automation e.V.

