



## Four-point contact ball bearing

Designation		Principal dimensions (mm)			Basic load ratings KN		Speed ratings rpm		Weight kg
Bearings with locating slots	Without locating slots	d	D	B	dyc Cr	stc Cor	Speed Ratings	Limiting Speed	
QJ202N2MA	-	15	35	11	12.7	8.3	22000	36000	0.062
QJ203N2MA	-	17	40	12	15.9	10.6	19000	30000	0.082
QJ303N2MA	-	17	47	14	23.4	15	17000	28000	0.14
QJ304N2MA	QJ304MA	20	52	15	29.6	20	15000	24000	0.18
QJ205N2MA	QJ205MA	25	52	15	25.1	20	14000	22000	0.16
QJ305N2MA	QJ305MA	25	62	17	39	28	12000	20000	0.29
QJ206N2MA	QJ206MA	30	62	16	35.1	28.5	12000	19000	0.24
QJ306N2MA	QJ306MA	30	72	19	49.4	38	10000	17000	0.42
QJ207N2MA	QJ207MA	35	72	17	46.2	39	10000	17000	0.36
QJ307N2MA	QJ307MA	35	80	21	59.2	46.5	9500	15000	0.57
QJ208N2MA	QJ208MA	40	80	18	52.7	45	9000	15000	0.45
QJ308N2MA	QJ308MA	40	90	23	71.5	58.5	8500	14000	0.78
-	QJ209MA	45	85	19	58.5	51	8500	14000	0.52
QJ309N2MA	QJ309MA	45	100	25	93.6	76.5	7500	12000	1.05
-	QJ210MA	50	90	20	61.8	56	7500	13000	0.59
-	QJ310MA	50	110	27	111	91.5	6700	11000	1.35
QJ211N2MA	QJ211MA	55	100	21	79.3	76.5	7000	11000	0.77
QJ311N2MA	QJ311MA	55	120	29	127	108	6000	10000	1.75
QJ212N2MA	QJ212MA	60	110	22	92.3	86.5	6300	10000	0.99
QJ312N2MA	QJ312MA	60	130	31	146	125	5600	9000	2.15
QJ213N2MA	QJ213MA	65	120	23	104	104	5600	9500	1.2
-	QJ313MA	65	140	33	165	146	5300	8500	2.7
QJ214N2MA	QJ214MA	70	125	24	114	114	5600	9000	1.32
QJ314N2MA	QJ314MA	70	150	35	186	166	4800	8000	3.15
QJ215N2MA	QJ215MA	75	130	25	117	122	5300	8500	1.45
QJ315N2MA	-	75	160	37	199	186	4500	7500	3.9
QJ216N2MA	QJ216MA	80	140	26	138	146	4800	8000	1.85
QJ316N2MA	-	80	170	39	216	208	4300	7000	4.6
QJ217N2MA	QJ217MA	85	150	28	148	160	4500	7500	2.25
QJ317N2MA	-	85	180	41	234	236	4000	6700	5.45
QJ218N2MA	-	90	160	30	174	186	4300	7000	2.75
QJ318N2MA	-	90	190	43	265	285	3800	6300	6.45
QJ219N2MA	-	95	170	32	199	212	4000	6700	3.35
QJ319N2MA	-	95	200	45	286	315	3600	6000	7.45
QJ220N2MA	-	100	180	34	225	240	3800	6300	4.05
QJ320N2MA	-	100	215	47	307	340	3400	5600	9.3

QJ222N2MA	-	110	200	38	265	305	3400	5600	5.6
QJ322N2MA	-	110	240	50	390	475	3000	4800	12.5
QJ224N2MA	-	120	215	40	286	340	3200	5000	6.95
QJ324N2MA	-	120	260	55	390	490	2800	4500	16
QJ226N2MA	-	130	230	40	296	365	2800	4800	7.75
QJ326N2MA	-	130	280	58	423	560	2600	4000	19.5
QJ228N2MA	-	140	250	42	325	440	2600	4300	9.85
QJ328N2MA	-	140	300	62	468	640	2400	3800	24
QJ230N2MA	-	150	270	45	377	530	2400	4000	12.5
QJ330N2MA	-	150	320	65	494	710	2200	3600	29
QJ232N2MA	-	160	290	48	423	620	2200	3800	15.5
QJ332N2MA	-	160	340	68	540	815	2000	3400	34.5
QJ234N2MA	-	170	310	52	436	670	2200	3400	19.5
QJ334N2MA	-	170	360	72	618	965	1900	3200	41.5
QJ236N2MA	-	180	320	52	449	710	2000	3400	20.5
QJ336N2MA	-	180	380	75	637	1020	1800	3000	47.5
QJ338N2MA	-	190	400	78	702	1160	1700	2800	49
QJ240N2MA	-	200	360	58	540	915	1800	3000	28.5

**Changzhi TEBearing Corp., Ltd.**

1 Huafeng North Road Changzhi city, Shanxi province, China

Tel: +86 355 3022969

Mobile: +86 18635527655

Skype: shawwinliu

[Email: tebearing@aliyun.com](mailto:tebearing@aliyun.com)

[shawwin@tebearing.com](mailto:shawwin@tebearing.com)

[Skype: shawwinliu](https://www.skype.com/add?contact=shawwinliu)

[www.tebearing.com](http://www.tebearing.com)

<http://te-bearing.en.alibaba.com>