



The CML RV Series is tailored to meet from low to high volume production requirements. With the RV series, you get the features you need, without paying for extras you don't. The RV 500 series features a heavy-duty Multi-Rip saws with higher horsepower ratings for higher volume customers. The RV 700 and RV1000 are heavy-duty machines with even more horsepower that provides a wider cutting area possibilities with an high volume environments. Whatever your requirements, Cml offers a Ripsaw to meet your needs.

CML

Cml has industry-leading ripsaws to help you successfully optimize the use of all material. Designed to meet your unique production requirements, the high performance CML multi-rip saws optimize materials and minimize costs. CML multi-rip saws deliver high quality cuts with limitless application possibilities. Whatever your requirements. CML has a ripsaws to help you make the most of every situation.

Cml Features

- Heavy-duty Dip chain feed belt with hardened steel guides
- 4 top idraulic pressure roller with Extended pressure board
- Precision surface treated Arbour shaft
- Easy and practical operation clearly displayed via the control panel
- Complete range of optimization solutions

CML ENGINEERING S.R.L.
 Advanced Equipment
 Intelligent Integration
 Experienced Consulting
 Incomparable Services
 E-mail info@cml-engineering.it



Technical Specifications	CML Multilame RV500
Voltage	400V / 50Hz
Dust Connection (MAIN)	300mm diameter port/30 meters per second/7600Mc3/h
Machine Weight	11.000 Kg
Machine Dimensions	Lenght 230cm
	Width 540cm
	Height 205cm
Main Drive Motor	Hp 30-40-50-60 / Kw 22-30-37-44
Feed Belt Motor	4Kw
Feed Belt Speed	0 a 50 Mt/1"
Maximum pass thru width	1000mm
Feed belt width	700mm
Maximum Balde speed	3500 RPM
Maximum board Thickness	120mm
Minimum board Length	900mm (400mm per optional pezzi corti)
Maximum distance between external blades	500mm (370mm blade)
Table working height from floor	780mm
Sound enclosure padding for quite running reducing noise level 15db	
Automatic oil pump for feed chain with failure detection shutoff	
Specifications are subject to change.	



Main Office : Via Torri Bianche 1 - 20059 VIMERCATE (MI) – ITALY

Production : Via G. Galilei, 34/36 – 20060 GESSATE (MI) - ITALY

Tel 0039-02-95384207

Fax 0039-02-95384223

E-mail : info@cml-engineering.it – Web : www.cml-engineering.it