

## Advanced Series

## Multi-Rip saws SCA 220 T 250



The CML Advanced Series is tailored to meet from low to high volume production requirements. With the Advanced Series, you get the features you need, without paying for extras you don't. The SCA 220 T 250 series features a heavy-duty Multi-Rip saws with higher horsepower ratings for higher volume customers. The SCA320 T 350, SCA 450 T 500, SCA 650 T 700 are heavy-duty machines with even more horsepower that provides a wider cutting area possibilities with an high volume environments. Whatever your requirements, Cml offers a Ripsaw to meet your needs.

### CML

Cml has industry-leading ripsaws to help you successfully optimize the use of all material. Designed to meet your unique production requirements, the high performance CML multi-rip saws optimize materials and minimize costs. CML multi-rip saws deliver high quality cuts with limitless application possibilities. Whatever your requirements, CML has a ripsaws to help you make the most of every situation.

### Cml Features

- Heavy-duty Dip chain feed belt with hardened steel guides
- 5 top pressure roller with Extended pressure board
- Precision surface treated Arbour shaft
- Easy and practical operation clearly displayed via the control panel
- Complete range of optimization solutions

**CML ENGINEERING S.R.L.**  
Advanced Equipment  
Intelligent Integration  
Experienced Consulting  
Incomparable Services  
E-mail [info@cml-engineering.it](mailto:info@cml-engineering.it)



## Advanced Series

## Multi-Rip saws SCA 220 T 250

Technical Specifications	CML Multi-Rip Saw SCA 220 T 250
Voltage	400V / 50Hz
Dust Connection (MAIN)	250mm diameter port/30 meters per second/7600Mc3/h
Machine Weight	2800Kg
Machine Dimensions	Length 217.5cm Width 178cm Height 184cm
Main Drive Motor	Hp 20-25-30-40 / Kw 15-18,5-22-30
Feed Belt Motor	0.75 Kw
Feed Belt Speed	0 a 36 Mt/1' (0-50 Mt/1')
Pressure Roll Motor	0.75Kw
Maximum pass thru width	680mm (800 mm)
Feed belt width	250mm
Maximum Balde speed	3500 RPM
Maximum board Thickness	110mm (330mm Blade)
Minimum board Thickness	20mm
Minimum board Length	500mm (280mm with optional – small pieces)
Maximum distance between fixed blades	220mm
Table working height from floor	780mm
Sound enclosure padding for quite running reducing noise level 15db	
Automatic oil pump for feed chain with failure detection shutoff	
Specifications are subject to change.	



Main Office : Via Torri Bianche 1 - 20059 VIMERCATE (MI) – ITALY  
Production : Via G. Galilei, 34/36 – 20060 GESSATE (MI) - ITALY  
Tel 0039-02-95384207  
Fax 0039-02-95384223

E-mail : [info@cml-engineering.it](mailto:info@cml-engineering.it) – Web : [www.cml-engineering.it](http://www.cml-engineering.it)