

MORBARK® BEEVER™ M20R FORESTRY TRACK

FEATURES

- » TorqMax Plus compression system, hydraulic lift assist, variable force constant hydraulic down pressure system with additional manually applied hydraulic down pressure at the valve handle and sprocket driven bottom feed wheel
- » Directional flow discharge system with horizontal and vertical hydraulic positioning manufactured from abrasion resistant steel
- » 36" (91.44 cm) diameter x 33 3/8" (84.77 cm) wide drum with front pocket and six Babbitt-style knives with removable knife holders
- » Discharge clean out door on bottom
- » Steel guard enclosing valve bank and automatic feed system components
- » Live hydraulic system including: ball valve, pump, motor, and valve bank
- » Spanish and English safety decals
- » 312B Caterpillar undercarriage with 20" (500 mm) grouser pads

Other Specifications

- » Drum diameter: 36" (91.44 cm)
- » Drum width: 33 3/8" (84.77 cm)
- » Infeed Opening: 65" wide x 43" high (165 cm x 109.22 cm)
- » Throat Opening: 28" wide x 20" high (71.12 cm x 50.8 cm)
- » Frame: 2" x 10" tubular (5.08 cm x 25.4 cm)

OPTIONS


- » Custom paint and logo packages
- » Electronic fuel gauge
- » Forestry, rotating or top load discharge
- » Grate System



A 6' (1.83 m) infeed bed with live WDH-110 chain drive

Advantage 3™ Drum creates more uniform chips

Remote Control



SPECIFICATIONS

	US	METRIC
Chipping Capacity	20"	50.8 cm
Length	22'9"	6.93 m
Height	11'5"	3.48 m
Width	8'6"	2.59 m
Gross Weight	26,540 lbs	12,040 kg
Engine	CAT	
Horsepower	350 to 400 HP	260 to 300 kW
Fuel Capacity (tank)	74 gallons	280 litres
Hydraulic Oil	73 gallons	163 litres
Tracks	312B Caterpillar undercarriage	



MORBARK®

www.morbark.com

800.831.0042

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS

2/15/17