



WeatherPro® - SELECT

A 5 x 5 reinforcing Polypropylene scrim coated on both sides with a uniquely engineered polypropylene blend.

APPLICATIONS

Entry level transit wrap that is ideal for packaging solid sawn lumber, I-joists & beams, structural panels or other products. We can provide you with the coated woven protection you need to maintain product integrity throughout transportation, inspection and storage.

PRODUCT SPECIFICATIONS

Nominal Weave	5 x 5 ppi (19 x 19 tapes per 10 cm)
Coating	Two Sides PP @ 0.8 – 1.1 mil thickness, 22 - 27 g/m ²
Color	White/Black; White/Beige (Custom colors are available on request)
Weight	85.7 g/m ² ± 5% (2.53 oz/yd ² ± 5%) finished weight
Widths	Up to 3.86 m, 152"



TENSILE STRENGTH ASTM D751

Machine Direction	Force	110 lb	50 kg
Cross Direction	Force	100 lb	45 kg

TRAPEZOIDAL TEAR STRENGTH ASTM D4533

Machine Direction	Force	42 lb	19 kg
Cross Direction	Force	38 lb	17 kg

UV ACCELERATED WEATHERING ASTM G154 (More than 90% strength retained after 2,000 hours* exposure)

Mullen Burst ASTM D751	115 psi	1070 kPa
Nominal Thickness	4.2 mils	0.11 mm

Note: all values are +/- 10% * QUV A-340 lamps 8 hrs @ 60° C, 4 hrs condensation at 40° C
The test data is based on average taken over several production runs and should not be considered or interpreted as minimum or maximum values.
Values are typical data and not limiting specifications.

Effective Date: February, 2019

800.567.9727
info@interwrap.com

www.interwrap.com