







## Dedicated gullet design: increased chip expulsion.

The special gullets are designed to direct more sawdust aside with the support of the internal rakers slots. The blade stays cleaner for longer. therefore limiting the dull-wear of the cutting edges.

## Perma-SHIELD coating: extreme lifetime.

The complete thermal insulation which conveys the highest resistance to heat and wear for an exceptional cutting quality. It strongly reduces resin buildup for a most performing blade which lasts longer.

## Flat tooth in K10S Carbide: the best combination for soft wood cutting.

The flat tooth is made of a powder mix with the highest impact strength level for cutting soft wood even in presence of knots.

	HW K10S
<b>b</b>	27.

Tooth features - Caratteristiche del dente

D	В	b	d	Z	NL - KN	Code	SAP
mm	mm	mm	mm		FT - CH	Codice	SAP
350	3,9	2,5	50	18+2+2	-	LM1035001	F03FS07701
400	4,4	3	50	18+2+2	-	LM1040001	F03FS07702
450	4,8	3	50	18+2+4	-	LM1045001	F03FS07703
500	5,2	3,5	50	18+2+4	-	LM1050001	F03FS07704
560	5,5	3,5	50	18+2+4	-	LM1056001	F03FS07705
300	3,3			10.2.4		LIVIZOSOCOT	1031307703

Suitable for Poplar, Pine, Spruce, Cedar, Larch.



freud S.p.A. - Società Unipersonale Via Padova, 3 - 33010 Tavagnacco (UD) Italy Tel. +39 0432 551411 - Fax +39 0432 551440 info@freud.it - www.freud.it