

‘Aircenter’ for FAD up to 2.5 m³/min

Space-saving, efficient compressed air production

No matter whether for a smaller business where space is at a premium, or a larger business requiring a decentralised compressed air supply, Kaeser’s compact "Aircenter" systems are the perfect choice for an efficient and environmentally-friendly source of quality compressed air. With a minimal footprint of approximately 1m², these energy saving systems are available for FADs from 0.34 to 2.5 m³/min at 8 bar and also provide application-specific compressed air treatment and storage.

All "Aircenter" models are characterised by their exceptional efficiency and there are now new versions of the two largest models, the "Aircenter 22" (11 kW) and the "Aircenter 25" (15 kW). At the heart of these systems lies an optimised SK series rotary screw compressor from Kaeser. With a maximum FAD of 2.5 m³/min (at 8 bar) these new SK models deliver up to 11 and 14 percent more compressed air, respectively, than their predecessors. This impressive performance boost has been achieved both through airend optimisation and the minimisation of internal pressure losses. In turn, these improvements have led to a reduction in specific power of up to 5 percent. The use of premium efficiency IE3 electrical motors has also contributed to additional energy savings. A further important efficiency-enhancing component is the new "Sigma Control 2" internal controller: This advanced system not only enables demand-oriented performance matching and dependable monitoring, but ensures

even greater flexibility through its numerous interfaces and innovative plug-in communication modules. Therefore, connection to energy-saving master control systems, computer networks and / or remote diagnostics and monitoring systems, such as Kaeser's Teleservice facility, couldn't be easier. The addition of an integrated RFID reader ensures service continuity, increases security and significantly raises service quality.

Moreover, all models share logical and user-friendly design throughout. For example, the left enclosure panel can be removed in a few simple steps and allows excellent visibility of the system's intelligently laid out components. As one might expect, all service points are easy to access. With the sound-damping enclosure panels in place, the already low operational sound levels from these compressors are reduced to a super-quiet background hum. In addition, the enclosure features four inlet openings for separate airflow cooling of the compressor, the motor and the switching cabinet and for compressor intake air. Kaeser's unique cooling system is equipped with a patented premium-efficiency dual-flow fan with separate cooling air flows for the motor and compressor. This not only achieves optimum cooling performance, low compressed air discharge temperatures and minimal sound levels, but also promotes efficient air compression.

The space-saving combination of a compressor, a thermally shielded refrigeration dryer and an underslung 350-l air receiver provides dependable and efficient compressed air production, treatment and storage within a single unit. As you might expect from a leading compressed air system provider such as Kaeser, these versatile units can also be equipped with air filters as required. The "Aircenter 22" and "Aircenter 25" are also available with an integrated frequency converter ("Sigma Frequency Control" - SFC) for applications where speed control is an advantage.

The smaller "Aircenter" models are based on Kaeser's SX or SM series rotary screw compressors. Equipped with a 200-l or a 270-l air receiver, these versions cover FADs from 0.34 to 1.5 m³/min (at 8 bar) and ensure super-quiet, efficient performance. As with the two largest models, 11- and 15-bar versions are available for applications requiring larger volumes of compressed air. Furthermore, the "Aircenter 12" can also be equipped with variable speed control.



Users who require not just an efficient compressor, but an all-in-one, compact compressed air system need look no further than an “Aircenter” system from Kaeser. True to Kaeser’s “Plug and Work” maxim, every model is ready for immediate operation once connected to the electrical supply and compressed air distribution network.

Datei: A_Aircenter_de

4.278 keystrokes – Approved for publication, copy appreciated

Bild:



Covering a free air delivery range from 0.26 to 2.55 m³/min (at 8 bar), Kaeser’s “Aircenter” series models provide dependable and efficient compressed air production, treatment and storage within a single compact unit (“Aircenter 22” shown in image).