

WEIPINMECH INT'L CO., LTD.





ENDLESS BELT

The endless belts without tearing problem at junction and surface patterns have an extremely high coefficient of friction and covered with varying degrees of Shore Hardness. WEIPINMECH provides a range of belts which high quality materials used together with modern technology for Sanders, Grinders, Planers etc.

1. Product Specification

Type	Color	Hardness	Max. Production Width	Description
CI 15	black	50°	1350mm	Even surface with good resistance to pressure and good grip.
EL 25		60°		Excellent adhesive properties.
RH 20				Very good grip in vacuum systems.
PL 10				Especially good for precision processing (could be punched with hole).

2. Surface Pattern

CI 15	EL 25	RH 20	PL 10
concave circle	convex ellipse	concave diamond	smooth surface
			

3. Composition Description

Type	Ply	Work load (Da N/cm)	Thickness ± 0.5mm	Min. roller diameter Ø (mm)
CI 15 EL 25	2	12	7.5	90
CI 15 · RH 20 EL 25 · PL 10	3	22	9	120
RH 20	4	30	10	150



WEIPINMECH INT'L CO., LTD.

1F., No. 88, Dafu Rd., Shen Kang Dist., Taichung 429, Taiwan
TEL: 886-4-25123942 FAX: 886-4-25120828
E-mail: weipin88@ms77.hinet.net