RiEPE®

www.riepe.eu

MADE IN GERMANY

FLUSH CUTTER   CROSS CUT SAWS   PRESSURE ZONE   PRE-MILLING UNIT

| CLEANING AGENT LP 163/93 ® | RELEASE AGENT NFLY ® | ANTISTATIC COOLANT LP 289/99 ® | RELEASE AGENT NFLY ® | RELEASE AGENT LPZ/II ® or TH97 ® (high heat resistant) | RELEASE AGENT LP 113/03 ® |

ORIGINAL RIEPE®

Chemical Products for spraying systems

RELEASE AGENT LPZ/II ®

Area of application: Prior to the pre-milling

Spray onto the upper and lower edge area of the workpiece
✓ Prevents the adhesion of emerging glue onto the workpiece

CLEANING AGENT LP 163/93 ®

Area of application: Before buffing wheels/ surface scraper

Spray onto the upper and lower edge area of the workpiece
✓ Removal of release agent and loose glue residue
✓ Cooling of the edgeband and glue joint
✓ Matt radius of the machined edgeband re-matches the surface finish

RELEASE AGENT NFLY ®

Areas of application: various

(a) Intermittent application to the pressure roller
✓ Glue residues cannot adhere to the roller
(b) Spray directly onto the surface of the edgeband
✓ Avoidance of marking and damage
✓ Protective foil is protected and not removed from the edge
(c) Edge/protective foil automatically transfers the release agent to the slide shoes
✓ Glue residues do not adhere ✓ Prevents marking and friction
(d) Direct application onto the DUO scraper
✓ No clogging of the DUO scraper
(e) Application to the tooling
✓ Prevents fouling of the trimmers

ANTISTATIC COOLANT LP 289/99 ®

Area of application: After pressure zone

Spray onto the upper and lower edge area of the workpiece
✓ Statically discharges the edge area
✓ Cooling of the glue joint and hardening of the glue
✓ Tracers and workpieces remain free of chippings
✓ Tooling remains free of glue residue

Container (litre): 30 │ 200 │ 1000

Leading machine manufacturers work with and recommend **original RIEPE® products**

HOMAG   IMA   BIESSE   scm group   HOLZHER   OTT   BRANDT

FELDER   Hebrock Kantenanleimmaschinen   Fravol   CEHISA   BI-MATIC WOODWORKING MACHINERY   Nanxing 南兴®   FORM 4

Casadei INDUSTRIA   EBS s.r.l.   Vitap   Giben INTERNATIONAL S.p.A.   GRIGGIO WOODWORKING MACHINERY   essetre   el WOOD WOODWORKING MACHINERY   STEMAS

✓ **High-quality raw materials**

✓ **Guaranteed continuous finish quality**

✓ **Low consumption:**
   < 1 litre per fine nozzle per 5000 running metres

✓ **Not harmful to the environment or health**

✓ **Compatible with all commercially available edge bands and adhesives**