



WPR Srl

Via Indipendenza, 10
31027 Spresiano (TV) Italia
Tel: +39 0422 911849
Fax: +39 0422 911292
Mail: info@wpr.it

TAKA® Srl

Registered Office:
Galleria Firenze, 3/3A
36022 Cassola (VI) Italia
Production:
Via dell'Artigianato, 19/25
36064 Mason Vicentino (VI)
Tel: +39 0424 411166
Fax: +39 0424 411727
Mail: info@taka.it



NWM/NWMD IS THE IDEAL SYSTEM FOR PANEL LAMINATION!



NWM/NWMD

NWM/NWMD is the ideal single or double system for the lamination of panels up to 2200mm application width for wood, MDF and chipboard with PVC, CPL, PET, PETG, PP, ABS or paper foils. This machine features all the technological advantages of slot nozzle application of hot melt and HMPUR adhesives and is fully customizable with a wide range of technical extras in order to increase productivity.

NWM/NWMD OFFERS ALL THE ADVANTAGES OF SLOT NOZZLE APPLICATION:

INCREASED PRODUCTIVITY:
easy and fast cleaning that guarantees reduced time for maintenance

THE GLUE IS APPLIED
directly on the foil

SLOT NOZZLE APPLICATION
allows also the post-forming

HIGH PROFITABILITY:
uses lowest quantities of adhesive

GREAT AESTHETIC RESULTS:
mirror-finish

IDEAL APPLICATION PRECISION
for High Gloss foils

HIGH QUALITY: avoid contamination of the glue because it is not in contact with air



SLOT NOZZLE DETAIL



SERVOMOTORS DETAIL

LAMINATION OF MDF, CHIPBOARD AND WOOD

- 2308.28P**
- Excellent wettability
 - Long open time
 - Suitable for various foil types
 - Good initial bond strength

- 2308.1T**
- Excellent wettability
 - Excellent spreadability
 - High quality finish for high gloss panels
 - Immediately applicable with primer-less foils (PET and PVC)

- 2308.20**
- Excellent working speed
 - Strong initial bond strength
 - Ideal for foils without plasticizing agents
 - High penetration

ANTISTATIC BRUSH DETAIL

Open time [m.i]		Setting time [m.i]		Cross-linking Days		Application temperature °C		Packages Kg	
Sec		Sec							

25,000 +/- 5,000		8-11		2-3		120-150		2-20-200	

30,000 +/- 7,500		7-9		2-3		120-140		2-20-200	

35,000 +/- 5,000		45-55		3		120-140		2-20-200	