CE

Metric / Imperial

10 QUALITY ASSURANCE YEAR

- Dust Collection Hole x Suggested Power: ø125mm / ø5" x 5HP
- Pressure Roller / Dia.: 6pcs / ø70mm / ø2.8"
- Single Chain Conveyor
- Cast Iron Guide Rails 9 V-shaped Ways



- Machine Size (L x W x H): 1950 x 1265 x 1430mm / 77 x 50 x 56"
- Packing Size (L x W x H): 1990 x 1305 x 1530mm / 78 x 51 x 60"
- N.W. / G.W.: 973 / 1100kg / 2150 / 2430lbs
- Max. Workpiece Thickness: 85mm / 3.3"
- Min. Workpiece Length: 200mm / 7.9"
- Max. Workpiece Width (Fence in Left Position): 190mm / 7.5"
- Table Surface: 1700 x 800mm / 67 x 31"
- Spindle Speed: 4750rpm
- Spindle Power: 7.5HP (Optional 10HP)
- Feeding Power: 1HP (Optional 1HP Inverter)
- Saw Blade Dia. x Bore: ø305mm x 25.4mm / ø12" x 1"
- Feeding Speed (Variable): 12~24m/min / 39~79ft/min
- Feeding Speed (Inverter): 11~26m/min / 36~85ft/min (Optional)

Xtra Sharp
We Cut Straight!

www.XtraSharp.co

XtraSharp Machinery Co., Ltd.
No.145, Lane 565, Pu Tsu St.,
Feng Yuan, Taichung 42072, Taiwan

T: +886-4-2522 5898
F: +886-4-2524 5820
E: william@XtraSharp.co

M: +32 496 77 96 78 (Belgium)

Xtra Sharp

We Cut Straight!

COMPACT BOTTOM RIP SAW
SA-12 SERIES

-XP: CE Certification
-XS: UL/CSA Certification

Compact Bottom Rip Saw

User Experience

- **Profile:** Furniture manufacturer
- **Location:** Vietnam
- **Configuration:** 2 compact bottom rip saws in series
- **Material:** Pre-planed lumber on top and bottom surfaces
- **Cutting dimensions:** 90mm (W) x 50mm (H) x 1100mm (L)
- **Capacity:** 1090 PCS/hour @ 20m/min (Excluding loading time)

Machining Procedure



Sawing → Gluing → Assembly

For more details, visit XtraSharp.co